

## Locknut Sockets

- These high-grade truck wheel bearing locknut sockets are made of high-strength steel and resist rounding out.
- For manual use only, impact wrench voids warranty.
- **Order individually by item number.**



Item	Drive	Point	Opening Size
1901	3/4"	(6 pt.)	2-3/32"
1902	3/4"	(6 pt.)	2-3/8"
1903	3/4"	(8 pt.)	2-3/8"
1904	3/4"	(6 pt.)	2-9/16"
1905	3/4"	(8 pt.)	2-9/16"
1906	3/4"	(6 pt.)	3"
1907	3/4"	(8 pt.)	3"
1908	3/4"	(6 pt.)	3-1/4"
1909	3/4"	(8 pt.)	3-1/4"
1910	3/4"	(6 pt.)	3-1/2"
1911	3/4"	(8 pt.)	3-1/2"
1912	3/4"	(6 pt.)	3-7/8"
1913	3/4"	(8 pt.)	3-7/8"
1914	3/4"	(6 pt.)	4"
1915	3/4"	(6 pt.)	4-1/8"
1916	3/4"	(6 pt.)	4-3/8"
1917	3/4"	(8 pt.)	4-3/8"
1918	3/4"	(6 pt.)	4-7/8"
1919	3/4"	(8 pt.)	4-7/8"
1920	3/4"	(6 pt.)	2-1/4"
1921	3/4"	(6 pt.)	2-1/2"
1922	3/4"	(6 pt.)	2-5/8"
1923	3/4"	(6 pt.)	2-3/4"
1924	3/4"	(8 pt.)	3-3/8"
1925	3/4"	(8 pt.)	3-3/4"
1926	3/4"	(6 pt.)	3-3/4"
1927	3/4"	(8 pt.)	3-13/16"
1928*	3/4"	(6 pt.)	2-9/16"
1932	3/4"	(6 pt.)	2-7/8"
1933	3/4"	(8 pt.)	2-7/8"
1934	3/4"	(6 pt.)	3-1/8"
1935	3/4"	(8 pt.)	3-1/8"
1936*	3/4"	(6 pt.)	2-3/8"
1937	3/4"	(8 pt.)	2-3/4"
1938	3/4"	(8 pt.)	4-1/2"
1939	3/4"	(6 pt.)	5-1/4"
1940	3/4"	(8 pt.)	4-1/8"
1941	3/4"	(8 pt.)	4-13/16"

\*Fits special "rounded" hex nut found on Dana axles of some Ford trucks.

The following are metric size wheel bearing locknut sockets.

1950M	3/4"	(6 pt.)	54 mm
1951M	3/4"	(6 pt.)	55 mm
1952M	3/4"	(6 pt.)	60 mm
1953M	3/4"	(6 pt.)	70 mm
1954M	3/4"	(6 pt.)	71 mm
1955M	3/4"	(6 pt.)	80 mm
1956M	3/4"	(8 pt.)	82 mm
1957M	3/4"	(8 pt.)	90 mm
1958M	3/4"	(8 pt.)	94 mm
1959M	3/4"	(8 pt.)	106 mm
1960M	3/4"	(8 pt.)	110 mm
1961M	3/4"	(8 pt.)	120 mm
1962M	3/4"	(8 pt.)	100 mm

## Truck Pinion Sockets

We've designed and built these sockets to have the proper clearance for yoke and locknut assemblies on a variety of truck transmissions and differentials. The sockets have 3" of usable depth and are 4" long. Using the right tools saves time and effort and eliminates the need to destroy standard sockets by grinding them down to fit tight pinion clearances.

- For manual use only, impact wrench voids warranty.
- **To order individually use item number listed below.**

**No. 9814** – Comes complete with tool board and six sockets, 1975 thru 1980 listed below (No. 1981 is not included).



Item	Drive	Point	Opening Size
1975	3/4"	(6 pt.)	2"
1976	3/4"	(6 pt.)	2-1/8"
1977	3/4"	(6 pt.)	2-1/4"
1978	3/4"	(6 pt.)	2-3/8"
1979	3/4"	(6 pt.)	2-5/8"
1980	3/4"	(6 pt.)	2-3/4"
1981	3/4"	(6 pt.)	2-1/2"

## Budd Wheel Socket Set (5 piece)

- One each of the sockets listed below comes in a convenient storage box.
- The metric sizes work on the import truck Budd wheels, and the 1-1/2" hex is for American-made trucks with dual rear wheels.
- Extra-deep design lets you remove both nut and stud with just one socket.
- Useable with a 1" square drive impact wrench.
- **To order individually use item number listed below.**

**No. 1944** – Budd Wheel Socket Set comes complete with the five sockets listed below in a molded plastic case.



Individual Item	Drive	Opening Size
1945A	1"	35 mm hex
1946A	1"	38 mm hex
1947A	1"	41 mm hex
1948A	1"	33 mm hex
1949A	1"	1-1/2" hex