









2525 Power door skin remover and 2524 power door skin remover air

- Cuts through rounded door-hem edge, over body lines, and around corners to remove door skins.
- · Eliminates time consuming and messy grinding.
- 20 gauge capacity in steel and other common sheet metals.
- Cuts straight and to the left for round or square auto body patches.
- Compact, lightweight, one hand operation.

Power Door Skin Remover Air

Compatible with most existing air set-ups.

2525

Power Door Skin Remover

Use with minimum 14.4V 3/8" cordless or corded drill.

2525RB

Replacement Blades



- Designed to efficiently hem the edges of replacement door skins with speed and precision.
- Minimum manual tacking required.
- High impact ABS polymer anvil will not scratch or mar the replacement door skin.
- 20 gauge capacity in steel and other common sheet metals.

2527

Power Hemming Tool Air

Compatible with most existing air set-ups.

2527

Power Hemming Tool

Use with minimum 14.4V 3/8" cordless or corded drill.

2527RA

Replacement Anvil



2529 Power Quarter Panel Hemming Tool and 2528 Power Quarter Panel Hemming Tool Air;

- Easily bend and close wheel arc flanges on quarter panels.
- Replicates a hammer and dolly motion at high speed, with greater precision and faster
- Reversible hammer head allows folding of the flange and sealing of the seam.
- Hand peg provides smooth operation and controlled maneuverability.

Power Quarter Panel Hemming Tool Air

Compatible with most existing air set-ups.

2529

Power Quarter Panel Hemming Tool

Use with minimum 14.4V 3/8" cordless or corded drill.

2529RH

Replacement Hammer

2529RA

Replacement Anvil











2531

Power Shear Corrugated Metal

- Easily cuts body panels across sharper body lines as well as large and small corrugated sheet metal.
- 24 gauge capacity in steel and other common sheet metals.
- Cuts straight and to the left for round or square holes.
- Compact, lightweight, one hand operation.

2531RB

Replacement Blades



2535 Power shear 18 and 2534 power shear 18 air

- Easily cuts body panels, wide opening jaws also navigate thick plastic bumper profiles, rocker panels, and layered material.
- 18 gauge capacity in steel and other common sheet metals.
- Cuts straight and to the left for round or square auto body patches.
- Compact, lightweight, one hand operation.

2534

Power Shear 18 Air

Compatible with most existing air set-ups.

2535

Power Shear 18

Use with minimum 14.4V 3/8" cordless or corded drill.

2535RB

Replacement Blades



2537 Power shear 16 and 2536 power shear 16 air

- Heavy metal cutting performance with a 16 gauge capacity.
- The spiral foot allows for easy left, right, or straight cutting action.
- Outstanding accessibility and control at air speed.
- 5 position 0 to 90 degree adjustable head angle.
- Long life 4 sided cutting insert.

2536

Power Shear 16 Air

Compatible with most existing air set-ups.

2537

Power Shear 16

Use with minimum 14.4V 3/8" cordless or corded drill.

2537RB

Replacement Blades

HAMMER & DOLLY SETS



2541

Hammer & Dolly Set, 4-piece

- General Purpose Pick Hammer with Fiberglass Handle
- Cross Chisel Curved Hammer with Fiberglass Handle
- Light Dinging Spoon
- Toe Dolly Block
- Made in USA

2541-1

General Purpose Pick Hammer

2541-2

Cross Chisel Curved Hammer

2541-3

Light Dinging Spoon

2541-4

Toe Dolly Block



2543

Hammer & Dolly Set, 7-piece

- Cross Chisel Curved Hammer with Fiberglass Handle
- Shrinking Hammer with Fiberglass Handle
- Utility Pick Hammer with Fiberglass Handle
- Light Dinging Spoon
- Toe Dolly Block
- Heel Dolly Block
- General Purpose Dolly Block
- Made in USA

2543-1

Shrinking Hammer

2543-2

Utility Pick Hammer

2543-3

Heel Dolly Block

2543-4

General Purpose Dolly

2541-2

Cross Chisel Curved Hammer

2541-3

Light Dinging Spoon

2541-4

Toe Dolly Block





BODY SERVICE AUTOMOTIVE SPECIALTY TOOLS

SYNTHETIC BODY TOOLS



2479

Trim Wedge, 30mm

For safe removal of body trim safely without damage.



2480

Trim Wedge, 60mm

For safe removal of body trim - wider profile for larger pieces.



Bumping Tool Set, 3-piece

Door Aligner, Center Punch and Straightener -Available individually.



Combination Wedge Pry Tool

Designed to safely pry plastic automotive pin style fasteners.



2482

Pick Hammer, 120mm x 30mm

Blind Panel Removal Wedge

Synthetic hammers designed by body repair pros for precise and effective working, ease of use.

Designed to reach inside panel release points for blind removal support.



Pinch Seam Straightener

Designed to realign, and straighten pinch seams.



2483

Pick Hammer, 140mm x 40mm

Two - sizes for a variety of application



Stepped Lever Wedge

Designed to assist alignment of doors and glass



2490 Universal Hook

- Dual purpose hooking / prying tool.
- Designed to safely pry small bezel components from interiors without damage.



Single Spotweld Carbide Drill Bit

- High Speed Steel construction specially treated to maintain sharpness.
- Self Centering with 3 cutting points!
- Designed for Drilling through Spot Welds.



Spotweld Carbide Drill Bit Set, 5-piece

- Super Hard Titanium construction specially treated to resist dulling in hi temp environments.
- Designed for Drilling through Spot Welds.



with other repair tools.

SYNTHETIC BODY TOOLS



Spot Weld Breaker

Use with hammer to slice through panels after spot welds have been drilled.



2471

Trim & Bezel Tool

Trim panel pry tool - non-marring tool for many interior trim and bezel pieces.



2472

Window Trim and Molding Remover

Perfect for removal of fragile trim pieces like chrome window trim.



2473

Half Round Bumping Tool

- Designed to reshape rounded metal profiles
- Good performance in confined areas.



Heavy Duty Profile Straightening Tool

Designed to reshape straight profiles with minimal deflection



2475

Round Body Anvil

- Use on rounded surfaces.
- Rounded Chisel end to reshape small diameter round profiles.
- Wide striking area for accurate strikes.



2476

Curved and Flat Dolly

Designed for both curved and straight area shaping.



2477

Edge Straightener

- Use to straighten edges.
- Wide profile enhances professional finish.
- Perfect for doors, fenders and hoods.



2478 **Extended Reach Bumping Tool**

Designed for use on hard to reach areas such as door skins, panels, hood and deck lids.

Spectrum Solar 10W LED Work Light with **UV Top Light**

5550 Specifications

10W LED Work light with UV Top Light

LI-ION Rechargeable Battery -3.6V 2250 mAH, AC/DC

Charger Input AC 100 ~ 240V; 50/60Hz; DC12V ~ 24V

Power Output: 5.0V 1000 mAH Charger Time: 3.5 ~ 4.0 hours

Active Time: 2.5 hours

Storage Temperature: -4°F to 158°F;

-20°C to 70°C

Operating Temperature: 23°F to 122°F; -5° to 50°C PS: LED Sector: 170°

At 50 cm: 350 LUX (750 LM) Waterproof Grade IP65



Spectrum Trio9W LED Work Light with 3W

LED Top Light

5551 Specifications

9W LED Work light with 3W LED Top Light

LI-ION Rechargeable Battery -3.6V 2250 mAH, AC/DC

Charger Input AC 100 ~ 240V; 50/60Hz; DC12V ~ 24V

Power Output: 5.0V 1000 mAH Charger Time: 3.5 ~ 4.0 hours

Active Time: 3.0 hours

Storage Temperature: -4°F to 158°F;

-20°C to 70°C

Operating Temperature: 23°F to 122°F; -5° to 50°C

PS: LED Sector: 25° At 50 cm: 4000 LUX Waterproof Grade IP65

Spectrum 30+430 Pc. LED Work Light with 4 Pc. LED Top Light

5552 Specifications

30 Piece LED Work light with 4 Piece LED Top Light

LI-ION Rechargeable Battery -3.6V 2250 mAH, AC/DC

Charger Input AC 100 ~ 240V; 50/60Hz; DC12V ~ 24V

Power Output: 5.0V 1000 mAH Charger Time: 3.5 ~ 4.0 hours

Active Time: 4.0 to 5.0 hours

Storage Temperature: -4°F to 158°F; -20°C to 70°C

Operating Temperature: 23°F to 122°F; -5° to 50°C

At 50 cm: 2250 LUX Waterproof Grade IP65

PS: LED Sector: 15°

- AC/DC Rechargeable
- Li-lon battery
- Magnetic base
- Bright LEDs 50,000 hour life
- Adjustable 60° angle
- Slip resistant textured body
- Impact and water resistant
- · Limited Lifetime Warranty









BODY SERVICE AUTOMOTIVE SPECIALTY TOOLS





4549 Door Panel & Upholstery Tool Set Heavy-duty door panel and upholstery tools

4549-1 - removes window and door handle clips, and upholstery tucking.

4549-2 - V-notched door panel clip removal tool 4549-3 - U-notched door panel clip removal tool



Euro Door Handle Kit

Ford Mirror Removal Tool

the mirror assembly.

- This kit contains the tools needed to service most door hinges and door handles on Audi, Mercedes-Benz, Porsche, and Volkswagen vehicles.
- Kit includes: A ratchet wrench with three 12-point bits (4 mm, 8 mm, 10 mm), one T40 and one T45 TORX® bit; a T30 TORX® long handled driver; and a T20 TORX® T-handle driver.
- T30 driver, 14" long; T20 driver, 9-1/2" long; hex ratchet, 9-1/2" long.

Save shop labor time and cost by allowing mirror

to be removed without damaging or removing

Works on these outside door mirrors: Windstar, Crown Vic, Grand Marq, Marauder, Taurus, Sable, Mustang, Town Car, Ranger,

Excursion, Super Crew (F-250-F-550),

F-650, F-750, Escape, Thunderbird, Explorer,

Trac, Aviator, Dual arm mirror used on Excursion,

Mountaineer, Expedition, Navigator, F-150, E-Series van, LS, Explorer Sport, Explorer Sport

Super, Crew (F-250-F-550), F-650, F-750 • Also works on 1999 and newer Ford interior



6642 Trim Tool Kit, 11-Piece

Includes 11 specialty tools designed to remove trim strips, panels, wheel caps, bezels, liners, shrouds, fascia, and more.

- Tools are constructed of durable, impactresistant nylon that will not damage nonmetal interior trim surfaces.
- Cloth pouch rests flat on a dashboard or fender for easy access to tools and then folds up with tools inside for storage.
- Kit has multiple applications in the automotive, aviation marine, and other industries.



4551 Door Panel & Upholstery Tool Set

Heavy-duty U-notched and V-notched tools with stainless steel blades used for removing small door panels and upholstery clips.



4492

E-Clip Tool Set, 5-piece

- Dual operation tool: one end of tool releases e-clip; other end of tool installs e-clip.
- Tools fit four sizes of e-clips: 6 mm, 7 mm, 8 mm,
- Each tool easily locks into handle provided.



7827 Saturn Window **Glass Socket**

This specially designed socket enables you to easily remove the tricky fasteners that Saturn uses to hold window glass to the regulator in its car doors. Our

tool won't cause the damage that often results from makeshift methods.

- For use on 1991 to 2009.
- Accommodates a 3/8" drive ratchet and extension



Trim Fastener and Molding Removal Set

- Set includes five different sizes and styles of tools that allow easy removal of trim fasteners, moldings, and wheel hubs.
- Tools are made of plastic to prevent damage to trim, moldings, alloy wheels, or vehicle paint.
- Can be used on trim fasteners and moldings inside, or outside, the vehicle.



Professional Scraper Set, 3-piece

Scrapers feature polished, heat-treated, stiff, stainless steel blades. Handles are ergonomic twocomponent plastic and feature a non-slip grip and steel bolstered end.

• Packaged in a storage tray. Includes: 1-1/4" straight blade, 1-1/4" bent blade, and 2" straight blade.







AUTOMOTIVE SPECIALTY TOOLS



5945

Air Bag Release Tool Kit

- Use to remove the air bag module from the steering wheel
- Work on many GM, Ford and Mercedes Benz vehicles.

Applications:

539255 - Air Bag Release Tool

GM 1999-newer Chevrolet Impala, Lumina, Monte Carlo, Venture, Pontiac Bonneville, Grand Prix, Montana, Buick LeSabre, Century, Regal, Olds Intrigue, Cadillac El Dorado, Deville, STS, SLS

539254 - T30 TORX® Socket

Mercedes Benz Models 107,123, 124, 126, 129, 140, 163, 164, 170, 201, 202, 203, 208, 209, 210, 211, 215, 219, 220, 221 and 463.

539256 - Anti-Theft Socket

Ford 2000-'04 Taurus/Sable, 1999-'03 Windstar Van.



Ford Air Bag Simulator

When plugged into the vehicle harness connector, power is restored to simulate a complete circuit for diagnostic purposes.

7955 - Ford air bag simulator. Special oneohm resistor for use on air bags on Probe

7956 - Ford air bag simulator. Special twoohm resistor for use on 1993 and newer Ford system II air bags.



- Removes wiper arms on many foreign and domestic cars and light trucks.
- Will not damage wiper arm or hood cowling during removal.
- Simply place puller feet under wiper arm and tighten forcing screw against wiper shaft.



- This simple tool allows for work with the vehicle door open without the annoying door buzzer on.
- High tension spring can be placed in the door jamb to close the door buzzer switch typically found by the hinges.



4449





Windshield Spray Nozzle Needle

- Makes quick work of clearing obstructions from the windshield washer spray nozzle.
- Easily pierces corrosion or remove blockage.
- The barrel is knurled for grip and control.
- Threaded end caps keep the needle points covered when not in use. The pocket clip keeps the tool handy.



- Set includes: • Lock Knob Puller
- Slide Lock Linkage Hook
- Under Window Knob Puller
- Under Window Lock **Button Depressor**
- Under Window Slide Lock Puller
- Lockout Wedge
- Porsche Lock Button Depressor
- Toyota/Chrysler Key Hole Lever
- GM/Ford Linkage Slider



- Ford Vent Window Lever
- Vent Window Button Depressor
- Vent Window Lever Puller
- Bell Crank Thin Bar
- Bell Crank Wide Bar
- Mercedes/Vovlo Lock Linkage Puller
- 119-2 Gas Cap Key.
- Instruction Manual



4450

Lockout Tool Set, 6-piece

Set includes

- Lockout Wedge
- Lock Knob Hook
- Slide Lock Linkage Hook
- Toyota/Chrysler Key Hole Lever
- Vent Window Lever Puller
- Bell Crank Thin Bar
- Instruction Manual



Truck Windshield Wiper Puller, 18mm

- Designed to remove aluminum wiper arm from the steel stud that often galvanizes, locking the arm and stud together.
- Investment cast design is strong, easier to use, and saves time.
- Live center and more precise alignment save labor. Works on these and many other vehicles: Jeep Liberty, Grand Cherokee, Dodge Caravan, Stratus, Ram Diesels, Dakota & PT Cruiser, Chrysler LHS, Town & Country, Saturn Vue Buick Rendevous, Cadillac CTS, Ford Focus, Ford Windstar, Honda Civic, Odyssy Toyota Camry.









Steering Wheel Holder & Pedal Depressor Kit

- This kit has two applications: 1) holds steering wheel in position for alignment adjustments, and 2) depresses brake pedal for various brake checks, including brake lamp operation.
- Rod easily slides in actuator for fast, easy installation of tool on brake pedal or steering wheel. Simply hand squeeze the actuator to accomplish fine adjustments.
- Kit includes: actuator assembly; extension rod for actuator (use when depressing brake pedal); hook assembly (hooks on steering wheel when depressing brake pedal or holding steering wheel); and flat pad (rests on front seal when holding steering wheel).

4546-1 - Handle and Rod.

4546-2 - Steering wheel and pedal holder.



Spot Weld Cutter Set

- Use with electric drill or air drill to cut 5/16" and 3/8" spot welds.
- Cutter bits have cutting teeth on each end.
- Replacement kit No. 4485-1 consists of (3) 5/16" cutter bits; (3) 3/8" cutter bits; and (4) centering tips.



Screw Extractor Set

- · Removes broken studs and bolts.
- Includes ten guide bushings, five drill bits and five screw extractors with extractor nuts.
- Drill bits are left handed to help removal.

Telescopic Support

- Car hoods, or trunk lids with weak hinges or struts can sag or fall. The OTC 4705 securely holds these panels up and out of the way. Great tool for setting a hard cover on a pick-up box - turns a two
- Just 21" when collapsed to almost 48" when fully extended.
- A simple twist loosens the support for expansion. Twist in the opposite direction to lock in place at the desired length.
- · Rubber end caps prevent scratching and scuffing.



4602

Brass Punch Set (2 piece)

- Two large, brass non-sparking punches. Ideal for use near precision parts or in locations where sparks from ferrous metal could be hazardous.
- Includes an 8" punch (5/8" hex, tapered to 3/8") and 10" straight punch (3/4" dia., chamfered at both ends).

4383

Hole Punch Kit

- Easy, smooth operation. Will pierce up to 14 gauge steel.
- 7 sets punches and dies. Sizes: 3/32", 1/8", 5/32", 3/16", 7/32", 1/4", and 9/32"



Brass Hammer and Punch Set

- Brass-head hammer and punches are ideal to use where sparks from ferrous metals would be hazardous, or where precision metal parts could be damaged by steel tools.
- Hammer head weighs 24 oz.; brass drift punch is 10" x 3/4" diameter; brass tapered punch is 8" x 5/8" hex tapered to 3/8" diameter point.



Brass Hammer and Punch Set

- Brass-head hammer and punches are ideal to use where sparks from ferrous metals would be hazardous, or where precision metal parts could be damaged by steel tools.
- Two hammer head weighing 24 and 12 oz.
- Two tapered punches 14" x 5/8", 10" x 5/8".
- One hex tapered punch 8" x 5/8"
- Two drift punches 10" x 3/4", 8" x 1/2".
- Two pin punches 6" x 3/8", 4" x 1/4".







898A

Body and Fender Dent Puller

Often, the biggest time-consuming part of dent removal is the removal and installation of interior panels and upholstery. This tool eliminates those steps. Simply drill a hole at the base of the dent and thread in the tool's selftapping screw. A few sharp blows of the slide hammer will pull the dent out.

- Puller is 17" long with Pyralin handle grip.
- Replaceable self-tapping screw. Instructions included. 104427-PK5 - Replacement screws (5 pack).



Master TORX® Socket Set

52-piece, professional socket set in a blowmolded case

Hundreds of applications from front to rear on cars and trucks:

- Seat belt bolts
- Headlight bezels
- Interior and exterior trim screws
- Door strikers & latches
- Engine assemblies - Tail lamp lenses &
- Brake rotor bolts
- assemblies
- GM front-wheel drive front wheel
- Bumpers
- bearings - Truck box liners
- Styles available: TORX bit sockets, TORX PLUS bits sockets, tamper-resistant TORX bits, and TORX sockets for external bolts.
- Made from superior S2 steel to meet or exceed torque specifications.
- See Page 110 for more information.



4784 Profile Gauge, 10"

This 10" gauge provides an exact copy of a contour or profile needed during bodywork or fabrication. The plastic fingers will not scratch original finish.



Grip Wrench Adapters

- For grip wrenches using single-lead thread adjusting screw.
- Adapter threads onto a slide hammer with a 5/8"-18 thread.

205378 – Grip wrench threads onto a 7/16"–14 end of adapter for pulling use.

557479 – Grip wrench threads onto a 5/16"–18 end

of adapter for pulling use. 557480 - Grip wrench threads onto a 1/4"-20 end

of adapter for pulling use.



18403

Fin Straightener

- Clean and straighten condenser, evaporator and radiator cooling fins.
- · Compact design for confined spaces: the straightener head is 3-1/8" in diameter; the handle is 3-1/2" long.
- Includes 12 clearly marked combs

Wheel 1: 8, 9, 10, 12, 14, & 15 fins per inch Wheel 2: 10.5, 11, 13, 18, 20, & 22 fins per inch



4509

Straight-Blade Hose Cutter

- Cuts rubber hoses ranging from 1/4" to 1-1/2".
- Simply place hose in tool and squeeze handle
- Replacement steel cutter blade No. 4509-1 is available.

4509-1 - Replacement hose cutter blade.



Ratcheting Hose & PVC Cutter (Standard)

- Cuts hose and PVC up to 1-3/8" dia.
- Features metal frame and ergonomic handles for high leverage.
- Compound ratcheting action provides maximum cutting power.
- Will also cut cable and wires.



4412

Ratcheting Hose & PVC Cutter (Heavy Duty)

- Cuts hose and PVC up to 1-3/4" dia.
- Features metal frame and rubber padded ergonomic handles for high leverage and
- Compound ratcheting action provides maximum cutting power.
- Will also cut cable and wires.



4818

Multi-purpose Scissors

Will cut hose, wire and cables, wood dowel, PVC, and thin sheet metals in addition to general cutting. The hardened stainless steel blades have an angle ground into one that eliminates slipping when cutting round materials.



HYDRAULIC SPREADERS AND RAMS




Hydraulic Spreaders

- Included as standard equipment with our collision sets, these versatile hydraulic spreader tools are also available individually. Ideal for removing dents and creases, performing straightening jobs, or for use as a clamp. Makes working in tight spots easy.
- Maximum spread is 3-1/4"

9101B - 1/2-ton spreader with 1/4" NPT ram half coupler 9102 - 1/2-ton spreader with 3/8" NPT ram half coupler





Hydraulic Spreader, 1-ton Capacity

This hydraulic spreader is rated at a full 1-ton capacity at 10,000 PSI and that's enough for a wide variety of jobs. Working in tight spots is no problem—it needs only a 9/16" clearance to engage the jaws. With a big 4" spread, it's ready for a variety of applications: straightening work, removing dents and creases from sheet metal, or as a clamp. The device's spring-return jaws are made of high-strength alloy steel. It can be dead-ended at 4" spread under full load. Ideally suited to work with No. 4012 hand pump (not included).



Hydraulic Rams for Collision Repair Sets

These premium quality rams are designed for long, trouble-free service. Backed by a life-time warranty, they are ideal replacements for worn-out, leaky rams. They feature a special piston rod that permits their use with the snap-together components of OTC's collision repair sets, or with most similar competitive products.

4082A - 4-ton ram with 5" stroke and special piston rod end designed to fit most collision repair set components.

4083B - 10-ton ram with 6-1/8" stroke and special piston rod end designed to fit most collision repair set components.

Specifications	4082A	4083B
Min. height	10-7/8"	14-5/8"
Max. height	15-7/8"	20-3/4"
Spring return	Yes	Yes
Rod end dia.	.874"	1.310"
Max. operating. Pressure	8,950	8,950
Oil cap. (cu. in.)	4.97	13.69
Oil port	1/4" NPT	3/8" NPT



Hydraulic Rams for Collision Repair Sets

These premium quality rams are designed for long, trouble-free service. Backed by a two-year warranty, they feature a special piston rod that permits their use with the snap-together components of OTC Stinger's new collision repair sets, or with most similar competitive products.

9104B - 4-ton ram with 4" stroke and special piston rod end designed to fit most collision repair set components.

9110B - 10-ton ram with 6" stroke and special piston rod end designed to fit most collision repair set components.

Specifications	9104B	9110B
Min. height	10-3/8"	15"
Max. height	14-3/8"	21"
Spring return	Yes	Yes
Rod end dia.	.874"	1.310"
Max. operating. Pressure	8,950	8,950
Oil cap. (cu. in.)	4.97	13.69
Oil port	1/4" NPT	1/4" NPT







Indexing Pry Bar Set, 3-piece

- Sizes 10", 12" and 15"
- Indexible to 180° for better access.
- 14 locking positions for leverage in multipleapplications.
- Knurled handle assures a sure grip.
- Meets or exceeds ANSI specifications for pry bars

7172 - 10" Indexing Pry Bar

7173 - 12" Indexing Pry Bar

7174 - 15" Indexing Pry Bar



Slide Hammer Puller, Ten-Pound

This heavy-duty slide hammer puller gets tough with those really stuck parts. It has all the features of our smaller versions – heat treated, 24" long, and a 5/8"–18 threaded end to adapt to any of OTC's pulling attachments. The difference is the ten-pound hammer that gives you the extra muscle for really stubborn pulling jobs.



Basic Slide Hammer Units

May be used with an OTC internal pulling attachment (page 129), or with internal or external-internal threaded adapters (page 127).

1155 – Slide hammer unit is 24" long with a 5 lb. hammer, 5/8"-18 threaded end.

1156 – Slide hammer unit is 24" long with a 2-1/2 lb. hammer, 5/8"-18 threaded end.

Rolling Head Pry Bars

You'll have a lot of leverage using one of these rolling head pry bars. The long, tapered body will also serve as an aligning drift.

7162 - Pry bar; 6" long

7163 - Pry bar; 12" long

7164 - Pry bar; 16" long

7165 - Pry bar; 18" long



A lightweight source of directed heat offering 500°F and 750°F settings, and also has a "cold" setting. This handy heat gun is ideal for many applications, including:

- Fast heating/drying of materials.
- Quick curing/drying of epoxies.
- Applying shrink tubing.
- · Softening tubing for bending.
- Speed-drying of touch-up paint to eliminate "haze."
- Drying out condensation in motors, clutches, controls, etc.
- Shock-proof and cool-running with a tough housing, the unit weighs just 2-1/2 lbs.
- 115V 50/60 Hz.

Replacement parts

44997 - Switch assembly.

Handled Pry Bars

Heavy-duty pry bar made of tempered square steel that you can hit without damaging the handle.

- Black chrome striking cap allows hitting the bar without damage to the handle.
- Ergonomic handle dual durometer composite handle for user comfort; reduces hand fatigue.
- Polished tip with black oxide finish.
- · Long-life finish resists rust and wear during use.
- OTC Marathon Lifetime Warranty.

8203 - 3-piece handled pry bar set in gray molded tray. Includes 12", 18", and 24" sizes.

8206 - 6-piece handled pry bar set in gray molded tray. Includes 8", 12", 18", 24", 32" and 36" sizes

8208 - 8" handled prv bar

8212 - 12" handled

prv bar

8218 - 18" handled

pry bar

8224 - 24" handled prv bar

8232 - 32" handled pry bar

8236 - 36" handled

pry bar



Hose Removal Set, 6-piece

- Consisting of six (6) hose removal tools which consists of three (3) 10", soft-handled tools and three (3) 15", soft-handled tools, each with a hard end-cap.
- They are made of heat-treated, chrome steel with assorted tip shapes.
- Ergonomic handle design fits properly in the hand, allowing for easier holding of the tool.
- Hose removal tools can also be used on upper and lower radiator hoses, clips, washers, gaskets and other items.
- Packaged in a molded tray which can be placed in tool drawer.



EASILY REMOVE HOSES, CLIPS, WASHERS AND GASKETS

Short Pick, Long Pick and Hook Set (14-piece)

- Combines 8260, 8262 and 8263 sets.
- Packaged in molded trays which can be placed in tool drawer.



Similar to Ford T87P-19061-A, 415-001

7575

Ford Radio Removal Tool Kit

These dual-purpose tools release the retaining clips of a radio faceplate so you can pull the radio from the instrument panel. For use on 1987 to current Mustang; 1988 and newer Tempo/Topaz; 1989 to current Lincoln Continental; 1990 to current Taurus/Sable, Ranger/Bronco II, Probe, Lincoln Town Car, Mark VII, Crown Victoria/ Grand Marquis, Thunderbird/Cougar, F-series pickups and E-series vans; 1991 to current Explorer; 1995 to 2003 Windstar.



Deluxe Radio and Antenna Service Kit

- Eleven-piece kit in molded case.
- · Universal antenna wrench.
- Ford radio removal tool.
- Deep sockets to remove and install the tamper-proof radio nuts from many GM, Chrysler, and other aftermarket radios.
- Antenna nut sockets cover most import and domestic antenna nuts.





4712

Euro Radio Removal Tool Kit

- Includes the popular tools needed to remove the radio from the dash on the following European vehicles: BMW, VW, Audi, and Mercedes-Benz.
- · Easily removes the radio without damaging the radio or the dash panel.



4715

Deluxe European Radio Tool Set

- 18-piece set of tools used to remove radios on most European vehicles sold in the U.S.
- Quickly and easily removes the radio from the dash without damage to the radio or dash. Replacement Parts
- 4715-1 Removal Keys (4 pieces) Audi, Becker, Mercedes-Benz, VW.
- 4715-2 Removal Keys (2 pieces) Becker, Mercedes-Benz, Porsche.
- 4715-3 Removal Keys (2 pieces) VW.
- 4715-4 Removal Keys (2 pieces) Skoda.
- **4715-5** Removal Keys (2 pieces) Becker.
- 4715-6 Pentagon Wrench BMW.
- 4715-7 Bent U-hook (2 pieces) Blaupunkt.
- 4715-8 U-hook (2 pieces) Audi, Blaupunkt, Ford, Grundig, VW.
- 4715-9 Allen Hex Wrench BMW, Opel.



Long Pick and Hook Set (4-piece)

- Consisting of four (4), 6.5", soft-handled picks.
- They are sturdy, with both stainless steel shafts and tips, with assorted tip shapes designed for marking, removing o-rings, accessing snap ring sand other assorted applications.
- Ergonomic handle design fits properly in the hand, allowing for easier holding of the tool.
- Multi-use tools to scribe, align pierce, clean or remove o-rings, shaft seals, cv boot and motorcycle fork seals and dust hoods.
- · Packaged in a molded tray which can be placed in tool drawer.



Mini Pick and Hook Set - 4-piece

- Sturdy stainless steel points and shafts designed for marking, removing o-rings, accessing snap rings, and performing other tasks. Assorted angle tips allow you to reach awkward locations.
- Knurled shaft design enhances finger control for delicate jobs.



4676PN

Windshield Wiper Puller and Nozzle Needle Combo

- The puller removes wiper arms on many foreign and domestic cars and light trucks.
- · Will not damage wiper arm or hood cowling during removal.
- Simply place puller feet under wiper arm and tighten forcing screw against wiper shaft.
- The Nozzle Needle makes quick work of clearing obstructions from the windshield washer spray nozzle.
- Easily pierces corrosion or remove blockage.
- The barrel is knurled for grip and control.
- Threaded end caps keep the needle points covered when not in use.



4706

Universal Lift Support Clamp (pair)

- Easy-to-use clamps designed for placement on hood/lid strut rods preventing the body component from falling of sagging.
- Great for vehicles & shrouds with weak or dry
- Simply place over strut rod and tighten.
- Small design keeps access to the compartment unobstructed.



OTC BFH HAMMERS

- Indestructible handle never needs replacement!
- Ergonomic rubber grip handle reinforced with steel bars resists breaking while absorbing impact and vibration.
- Drop-forged head is induction-hardened for long life, and contains steel locking plates that are specially bonded to ensure the head never becomes loose.







OTC No.	Head Weight	Handle Length	Total Weight			
	Club/Hand Drill Hammer, Indestructible Handle					
5791ID-312	2.5 lbs.	12"	4 lbs.			
5791ID-412	4 lbs.	12"	5.1 lbs.			
5791ID-416	4 lbs.	16"	5.5 lbs.			
Cross Peen Hammer, Indestructible Handle						
5792ID-216	2 lbs.	16"	4.5 lbs.			
5792ID-316	3 lbs.	16"	5.4 lbs.			
Ball Peen Hammer, Indestructible Handle						
5793ID-2414	24 oz.	14"	2.6 lbs.			
5793ID-3214	32 oz.	14"	3.0 lbs.			



5912

Crimpwell™ Angled Crimping Pliers

- Universal crimping design accommodates soft wire – solid or stranded – 10-22 AWG.
- Cutting feature included for quicker preparation.
- 9" (228mm) in length, with protective grips to increase leverage and secure crimp.
- Angled design keeps the connector, the wire, and the crimper "in-line" – improving visibility and access in hard to reach places.
- Designed to not pierce connector insulation and also works on un-insulated connectors.
- Service tech can use as much force as desired to ensure connection and it will not damage connector insulation.
- Easy-to-use: Simply insert the connector into the crimping feature, slip over the connector and squeeze.



Self Adjusting Wire Stripper, 9"

- Strips insulating sheathing from wires ranging from 10 ga. to 22 ga.
- Easy-to-use, just insert wire and squeeze.
- Also cuts and crimps



5950A

CrimPro™ 4-in-1 Angled Wire Tool

- The angled feature allows access to close quarters and facilitates superior crimps.
- · Compact 7-inch design used 4 ways.
- Gripping nose to pull, twist, bend, and shape.
- Crimper crimps 12-20 AWG insulated and non-insulated wire.
- Stripper strips 12-20 AWG wire.
- Cutter ability to make cuts both above and below pivot.



5950S

CrimPro™ 4-in-1 Wire Tool

- Compact 7-inch design used 4 ways.
- Gripping nose to pull, twist, bend, and shape.
- Crimper crimps 12-20 AWG insulated and non-insulated wire.
- Stripper strips 12-20 AWG wire.
- Cutter ability to make cuts both above and below pivot.



4467

Automatic Wire Stripper

- Quick removal of insulation on wire AWG 12-20.
- Comes with adjustable depth gauge (8mm to 12mm).
- Sharp v-shaped tooth easily removes insulation without any damage to soft wire strands.
- Cutting tool stored below the stripper.
- Features a space saving locking mechanism for pockets or tool drawer storage.







Collision Repair Sets, Stinger Series 4- and 10-Ton

- · Very competitively priced, yet high quality sets include single-speed hydraulic hand pump, hose, and ram.
- Components snap together for quick setups to apply pushing, spreading.
- Components include: hydraulic pump, hose, and ram; ram flat base; extension tubes (4); 1/2-ton spreader; tube coupling; ram toe; wedge head; serrated saddle; flex head; plunger toe; 90° wedge head; storage case. The case for the 10-ton set has wheels for mobility.
- 1513B 4-ton collision repair set. Has single speed hydraulic hand pump and ram with 4" stroke.
- 1515B 10-ton collision repair set. Has single speed hydraulic hand pump and ram with 6" stroke.



- Components snap together, permitting you to apply pushing, spreading.
- Components include: hydraulic pump, hose, and ram; ram flat base; 1/2-ton hydraulic spreader; extension tubes (4); tube coupling; ram toe; wedge head; serrated saddle; flex head; plunger toe; 90° wedge head; storage case. The case for the 10-ton set has wheels for mobility.
- 1517A 4-ton collision repair set. Has single speed hydraulic hand pump (4000) and ram (4082B) with 5" stroke.
- 1519A 10-ton collision repair set. Has two-speed hydraulic hand pump (4004) and ram (4083B) with 6-1/8" stroke.
- 504888 Replacement quick coupler (external).
- 504889 Replacement quick coupler (internal).

Collision Repair Set, 10-Ton

- Exert hydraulic force just where it's needed to lift, spread, bend, or straighten. Handles the high-force jobs you face daily in trailer maintenance or other
- Includes reliable components including 10-ton, 10-1/8" stroke hydraulic ram; air/hydraulic pumping unit; hydraulic hose; four snap-together extension tubes; extension tube coupling; serrated saddle; flat base; 90° wedge head; flex head; storage case.
- All set components are covered by OTC Lifetime Marathon Warranty®.





FASTENER SERVICE AUTOMOTIVE SPECIALTY TOOLS



5900A

Master TORX® Socket Set

52-piece, professional socket set in a blow-molded case.

Hundreds of applications from front to rear on cars and trucks:

- Seat belt bolts
- Interior and exterior trim screws
- Engine assemblies
- Tail lamp lenses & assemblies
- Bumpers

- Headlight bezels
- Door strikers & latches
- Brake rotor bolts
- GM front-wheel drive front wheel
- bearings
- Truck box liners
- Styles available: TORX bit sockets, TORX PLUS bits sockets, tamper-resistant TORX bits, and TORX sockets for external bolts.
- Made from superior S2 steel to meet or exceed torque specifications.

Master Torx Socket Set includes:

TORX® Bit T6 to T60	Socket Set (15-piece)			S [®] Bit Socket 60 (12-piece)			ternal Socket (13-piece)			mper-Resista 50 (12-piece)	
Part No.	Size	Sq. Drive	Part No.	Size	Sq. Drive	Part No.	Size	Sq. Drive	Part No.	Size	Hex Insert
5906	T6	1/4"	5918	TP8	1/4"	5934	E4	1/4"	5919	TT8	1/4"
5908	T8	1/4"	6181	TP10	1/4"	5935	E5	1/4"	5920	TT10	1/4"
6101	T10	1/4"	6182	TP15	1/4"	6151	E6	1/4"	5921	TT15	1/4"
6102	T15	1/4"	6183	TP20	1/4"	6152	E7	1/4"	5922	TT20	1/4"
6103	T20	1/4"	6184	TP25	1/4"	6153	E8	1/4"	5923	TT25	1/4"
6104	T25	1/4"	6185	TP27	1/4"	6154	E10	3/8"	5924	TT27	1/4"
6105	T27	1/4"	6186	TP30	1/4"	6155	E12	3/8"	5925	TT30	1/4"
6106	T30	1/4"	6187	TP40	3/8"	6156	E14	3/8"	5926	TT40	3/8"
6107	T40	3/8"	6188	TP45	3/8"	6157	E16	3/8"	5927	TT45	3/8"
6108	T45	3/8"	6191	TP50	3/8"	5936	E18	1/2"	5928	TT50	3/8"
6109	T47	3/8"	6192	TP55	3/8"	5937	E20	1/2"	5929	TT55	3/8"
6110	T50	3/8"	6193	TP60	1/2"	5938	E22	1/2"	5930	TT60	1/2"
6111	T55	3/8"				5939	E24	1/2"			
6112	T60	1/2"									
6198	T70	1/2"									

6100 Standard TORX® Socket Set T10 to T60 (12-piece)

Set includes one each of the following:

No.	Size	Sq. Drive
6101	T10	1/4"
6102	T15	1/4"
6103	T20	1/4"
6104	T25	1/4"
6105	T27	1/4"
6106	T30	1/4"
6107	T40	3/8"
6108	T45	3/8"
6109	T47	3/8"
6110	T50	3/8"
6111	T55	3/8"
6112	T60	1/2"





6135 Universal Brake Caliper Socket Set (9-piece)

Set includes one each of the following:

No.	Size	Sq. Drive
6107	T40	3/8"
6108	T45	3/8"
6110	T50	3/8"
6112	T60	3/8"
6165	1/4"	3/8"
6167	3/8"	3/8"
6175	7 mm	3/8"
6176	8 mm	3/8"
6177	10 mm	3/8"





6145Tamper-Resistant TORX® Socket Set (7-piece)

Set includes one each of the following:

and read ming.				
No.	Size	Sq. Drive		
5920	TT10	1/4"		
5921	TT15	1/4"		
5922	TT20	1/4"		
5923	TT25	1/4"		
5924	TT27	1/4"		
5925	TT30	1/4"		
5926	TT40	3/8"		








Fraction Hex Socket Set (7-piece)

Set includes one each of the following:





Tamper-Resistant TORX® Plus Socket Set (11-piece)

S of

11-piece) et includes of the follow		Resistant TORX*Plus	
No.	Size	Sq. Drive	
5905-8	8IPR	1/4"	
5905-10	10IPR	1/4"	
5905-15	15IPR	1/4"	
5905-20	20IPR	1/4"	
5905-25	25IPR	1/4"	
5905-27	27IPR	1/4"	
5905-30	30IPR	1/4"	
5905-40	40IPR	3/8"	
5905-45	45IPR	3/8"	
5905-50	50IPR	3/8"	
5905-55	55IPR	3/8"	

Metric Ball Hex "L" Keys 1.5mm to 10mm (10-piece)

Set includes one each of the following:

	5
No.	Size
6952-1	1.5mm
6952-2	2mm
6952-3	2.5mm
6952-4	3mm
6952-5	4mm
6952-6	5mm
6952-7	6mm
6952-8	7mm
6952-9	8mm
6952-10	10mm



6170 Metric Hex Socket Set (7-piece)

Set includes one each of the following:

No.	Size	Sq. Drive
6171	3 mm	3/8"
6172	4 mm	3/8"
6173	5 mm	3/8"
6174	6 mm	3/8"
6175	7 mm	3/8"
6176	8 mm	3/8"
6177	10 mm	3/8"



5931 **External Torx® Plus** Socket Set (8-piece)

Set includes one each of the following:

No.	Size	Sq. Drive
5931-6	6EP	3/8"
5931-7	7EP	3/8"
5931-8	8EP	3/8"
5931-10	10EP	3/8"
5931-11	11EP	3/8"
5931-12	12EP	3/8"
5931-14	14EP	3/8"
5931-16	16EP	3/8"



6954 Standard TORX® "L" Keys T8 to T50 (10-piece)

Set includes one each of the following:

No.	Size
6954-1	T8
6954-2	T10
6954-3	T15
6954-4	T20
6954-5	T25
6954-6	T27
6954-7	T30
6954-8	T40
6954-9	T45
6954-10	T50



6150 External TORX® Socket Set (7-piece)

Set includes one each of the following:

01 1110 10	acounty.	
No.	Size	Sq. Drive
6151	E6 x 25	1/4"
6152	E7 x 25	1/4"
6153	E8 x 25	1/4"
6154	E10 x 32	3/8"
6155	E12 x 32	3/8"
6156	E14 x 32	3/8"
6157	E16 x 32	3/8"



XZN Super Short Socket Bit Set (8-piece)

Set includes one each of the following:

	9.	
No.	Size	Sq. Drive
5942-4	SP4	1/4"
5942-5	SP5	1/4"
5942-6	SP6	1/4"
5942-8	SP8	1/4"
5942-10	SP10	3/8"
5942-12	SP12	3/8"
5942-14	SP14	3/8"
5942-16	SP16	3/8"





TORX® Plus "L" Keys TP8 to TP50 (10-piece)

Set includes one each of the following:

	3
No.	Size
6956-1	TP8
6956-2	TP10
6956-3	TP15
6956-4	TP20
6956-5	TP25
6956-6	TP27
6956-7	TP30
6956-8	TP40
6956-9	TP45
6956-10	TP50



6180 **TORX® PlusSocket Set** (9-piece) Set includes one each

Size	Sq. Drive
TP10	1/4"
TP15	1/4"
TP20	1/4"
TP25	1/4"
TP27	1/4"
TP30	1/4"
TP40	3/8"
TP45	3/8"
TP50	3/8"
	TP10 TP15 TP20 TP25 TP27 TP30 TP40 TP45

6950

SAE Ball Hex "L" Keys 1/16" to 3/8" (10-piece)

Set includes one each of the following

No.	Size
6950-1	1/16"
6950-2	5/64"
6950-3	3/32"
6950-4	1/8"
6950-5	5/32"
6950-6	3/16"
6950-7	7/32"
6950-8	1/4"
6950-9	5/16"
6950-10	3/8"



6958 **TORX® TAMPER** RESISTANT "L" Keys TT8 to TT50 (10-piece)

Set includes one each of the following:

No.	Size
6958-1	TT8
6958-2	TT10
6958-3	TT15
6958-4	TT20
6958-5	TT25
6958-6	TT27
6958-7	TT30
6958-8	TT40
6958-9	TT45
6958-10	TT50







7365 Hex Key Wrenches

Allen head cap screws are everywhere, which makes a set of these wrenches a necessity.

- Extra long for added leverage and accessibility.
- Meets ANSI specs.
- Plastic pouch containing wrench Nos. 7345 through 7354.

Tool		Fits Set	Fits HH Cap
No.	Size	Screws	Screws
7345*	1/16"	6	-
7346*	5/64"	8	_
7347*	3/32"	10 & 12	-
7348*	1/8"	1/4"	8
7349*	5/32"	5/16"	10
7350*	3/16"	3/8"	1/4"
7351*	7/32"	7/16"	5/16"
7352*	1/4"	1/2"	3/8"
7353*	5/16"	5/8"	3/8" & 7/16"
7354*	3/8"	3/4"	1/2"
7355†	7/16"	13/16"	9/16"
7356†	1/2"	7/8"	5/8"
7357†	9/16"	1"	3/4"
7358†	5/8"	1-1/4" & 1-3/8"	1"
7359t	3/4"	1-1/2"	1-1/8" & 1-1/4"
7360†	1"	1-3/4" & 2"	1-1/2"

- * Included in No. 7365 set.
- † Available separately; not included in set.



- Specially designed socket is needed to tighten or loosen head bolts on Toyota Paseo vehicles with 3S-GE and 3S-FE engines.
- 8 mm socket features a 12-point, 1/2" drive socket.



7334 Metric Hex Key Wrench Set

These long-arm hex key wrenches provide added leverage and accessibility.

- Rust-resistant black oxide finish.
- There are 9 sizes, from 1.5 mm to 10 mm.
- Available separately: 12 mm, 14 mm, 17 mm, and 19 mm.
 Metric hex key set in plastic pouch. Sizes: 1.5 mm, 2 mm, 2.5 mm, 3 mm, 4 mm, 5 mm, 6 mm, 8 mm, and 10 mm.

Tool	Size
No.	(mm)
7321*	1.5
7322*	2
7323*	2.5
7324*	3
7325*	4
7326*	5
7327*	6
7328*	8
7329*	10
7330 †	12
7331†	14
7332†	17
7333 †	19

- * Included in No. 7334 set.
- † Available separately; not included in set.



6986 Stud Remover Set, Fractional

This fractional, 4-piece, stud remover set offers the best professional extractors available. Designed and tested to reach studs in difficult work areas.

• Housed in a blow-molded storage case. 3/8" drive for:

6986-1 – 1/4" stud remover **6986-2** – 5/16" stud remover

1/2" drive for:

6986-3 – 3/8" stud remover **6986-4** – 7/16" stud remover



4651

Screw Extractor Set

- Removes broken studs and bolts.
- Includes ten guide bushings, five drill bits and five screw extractors with extractor nuts.
- Drill bits are left handed to help removal.



This metric, 4-piece stud remover set offers the best professional extractors available. Designed and tested to reach studs in difficult work areas.

• Housed in a blow-molded storage case. 3/8" drive for:

6987-6 – 6 mm stud remover **6987-8** – 8 mm stud remover

1/2" drive for:

6987-10 – 10 mm stud remover

6987-12 - 12 mm stud sizes.



FOR PRODUCT VIDEOS VISIT OTCTOOLS.COM



- Socket is designed to fit in the cylinder head on M42 and M50 engines to remove and install cylinder head bolts.
- Spring loaded detent ball holds bolt in place.
- Works with 1/2 inch ratchet, breaker bar, or torque wrench. Socket size is E12 for external TORX® bolts.





Impact Drivers

- · Loosens hard-to-turn screws, bolts or nuts.
- Handle design prevents possibility of hitting hand with hammer when striking impact driver.
- Bit holder has 3/8" drive (No. 4608), 1/2" (No. 4607) drive, and 5/16" hex for Phillips and flat screwdriver bits.
- Includes eight screwdriver bits:

No. 2 Phillips bit, 1-3/8" long with 5/16" hex No. 2 Phillips bit, 3-1/8" long with 5/16" hex No. 3 Phillips bit, 1-3/8" long with 5/16" hex

No. 3 Phillips bit, 3-1/8" long with 5/16" hex

5/16" wide x 1-3/8" long with 5/16" hex slotted bit

5/16" wide x 3-1/8" long with 5/16" hex slotted bit

3/8" wide x 1-3/8" long with 5/16" hex slotted bit 3/8" wide x 3-1/8" long with 5/16" hex slotted bit

4607 - 1/2" Impact Driver 4608 - 3/8" Impact Driver



4576

Universal C-Frame Nut Splitter

- Forged and heat-treated frame with offset handle works where ordinary nut splitters may fail. Smooth action cracks nuts without damaging bolt threads.
- Chisel rotates to line up parallel to bolt. Splits non-heat-treated nuts of 7/16" (11 mm) through 3/4" (19 mm) diameter. Tool is 6-3/4" in length.



Universal Outside Thread Chaser

Quickly restore threads to near new condition without expensive thread cutting equipment. • Use for 1-1/4" to 5" O.D.

7402 - Thread chaser, includes Standard Die Set 216884. 6 dies, threads per inch - 4, 5, 6, 7, 7-1/2, 8, 9, 10, 11, 11-1/2, 12, 14, 16, 18, 20, and 24.

Replacement V-pads and Die Sets:

216884 - Standard die set. Includes 6 dies, threads per inch - 4, 5, 6, 7, 7-1/2, 8, 9, 10, 11, 11-1/2, 12, 14, 16, 18, 20, and 24.

202817 - Metric die set. Includes three dies: 1 mm- 1.25 mm-1.5 mm-1.75 mm, 2 mm-2.5 mm-3.0 mm-3.5 mm; 4 mm pitch dies.

206803 - V-pad.



4614

Side Terminal Battery Wrench

- · Designed for use on GM side-terminal batteries, or any 5/16" hex head battery bolt.
- 5/16", 6 point, box end, 5-1/2" long, ratcheting wrench; insulated handle.



4615

Long-Side Terminal Battery Wrench

- Designed for use on GM side-terminal batteries, or any 5/16" hex head battery bolt.
- · Long handle allows access to hard-to-reach battery terminal bolts.
- 5/16", 6 point, box end, 10" long, ratcheting wrench; insulated handle



4616

Battery Terminal Wrench - 10mm

- Designed for use on 10 mm battery terminal bolts found on many import and domestic vehicles.
- 10 mm, 12 pt., box-end ratcheting wrench; 5-1/2" long with insulated handle



Spanner Wrench, 3/4" - 2"

This chrome vanadium hardened steel wrench features a 5" handle and slim strong hook to access slotted retaining rings in hard to reach areas.



Spanner Wrench, 2" - 4 3/4"

This chrome vanadium hardened steel wrench features a 9" handle and slim strong hook to access slotted retaining rings in hard to reach areas.



Adjustable Hook Spanner Wrench

Here's a tool that's needed wherever turret adjusting nuts or packing gland nuts are used.

- Capacity is 1-1/2" to 4".
- Handle is 24" long, 11/16" diameter.



Adjustable Hook Spanner Wrenches

These pieces will replace many fixed-size wrenches needed to service industrial tractors and other equipment. Their drop-forged jaws adjust to 11 positions for a capacity of 4-3/4" to 12-3/4" O.D

• Handle is 24" long and 1" in diameter.

7307 - Spanner wrench with one 3/8" thick

7308 - Spanner wrench with two interchangeable jaws: one 3/8" thick, one 3/4" thick



Heavy-Duty Adjustable HookSpanner Wrench

Some jobs require beefier tools. Here's a wrench to fill that need. It's drop-forged and features extra heavy construction and a 3/4" thick, 11-position hook jaw that's capable of gripping fasteners from 4-3/4" to 12-3/4" O.D.

• Handle is 25-3/4" long and 15/16" in diameter.



Dial Torque Wrench

- Torques in both right and left hand directions with equal accuracy.
- Can be used with confidence in all automotive, and industrial applications.
- Reads directly in both English and Metric graduations.
- Wrench can be held at any point without affecting accuracy.
- Memory or follow-up pointer can be utilized to indicate the maximum torque reached.
- Accuracy; +/- 4% CW and CCW.
- Torque Range; 0-150 in. lbs. (0-17 N-m).
- 3/8" square drive, 10" length.
- Includes blow-molded storage case.

Tool No.	Torque Range	Graduations	Square Drive	Lengt
7380	0-150 in. lbs. (0-17	4 in. lbs.	3/8"	10"
	N•m)			





FASTENER SERVICE AUTOMOTIVE SPECIALTY TOOLS





Torque Multiplier, 1000 ft-lb

- Drive Input; 1/2", 365 lb-ft Max
- Drive Output; 3/4", 1100 lb-ft Max
- Head Width: 2.9", 3.3:1 Ratio
- Reaction Bar; 13-3/4"
- · Includes reaction foot.
- Note; frictional gear loss = 6%



7368

Torque Multiplier, 2000 lb-ft

- Drive Input; 3/4", 730 lb-ft Max
- Drive Output; 1", 2200 lb-ft Max
- Head Width; 3.6", 3.3:1 Ratio Reaction Bar: 15-5/8
- Includes reaction foot.
- Note: frictional gear loss = 6%

Torque Angle Gauge

 Required when servicing many late model engines that use torque-to-yield fasteners. Measures angle of rotation after pre-torque in torque-angle applications.



- The 360° scale is marked in 2° increments and intervals of 10° and 30°; easily zeroed for next application by turning the tool housing.
- Has 1/2" male and female square drives.

7415

Torque Angle Gauge

Many manufacturers specify a torque angle procedure for tightening fasteners and head bolts because it helps ensure more accurate tightening. This torque angle gauge, featuring an easy-to-read gauge, will provide a precise reading.

• Accommodates a 1/2" drive torque wrench.





Torque Multipliers

These 4:1 ratio torque multipliers provide the power to tighten threaded fasteners in a number of truck and tractor repair operations.

5073 – **1,000 lb. capacity torque multiplier**. Has 1/2" square drive and 3/4" square drive output. Includes 14" extension handle.

5074 - 2,000 lb. capacity torque multiplier.

Has 3/4" square drive and 1" square drive output. Includes 18" extension handle.



Preset Torque Wrench Set

These color coded click torque wrenches are pre-set to the most common lug nut torque settings, making them perfect for tire shops. Highly durable design can hold up to the toughest tire shop demands.

- No need for adjustments
- Durable satin finish
- 1/2" Drive, 36 tooth
- Quick release ratchet head
- Perfect for Wheel / Tire shop
- Accuracy better than ±3% CW Sold Individually:

Preset Torque Wrench, 1/2" 65 lb-ft

5776-2

Preset Torque Wrench, 1/2" 80 lb-ft

Preset Torque Wrench, 1/2" 100 lb-ft

5776-4

Preset Torque Wrench, 1/2" 120 lb-ft

Preset Torque Wrench, 1/2" 140 lb-ft



Giant Adjustable Wrenches

The really big jobs call for really big tools. These wrenches will handle 42 bolt sizes from 1-3/8" to 4-3/4". Together, both wrenches weigh just 41 lbs., but can replace over 1,000 lbs. of fixed-size wrenches

7640 – Giant adjustable wrench. Rated to withstand 2,000 ft. lbs. of torque.

7641 - Giant adjustable wrench. Rated to withstand 5,000 ft. lbs. of torque.

Tool No.	Nut / Bolt Size	Increments of Jaw Adjustment	Lgth.	Head Thickness	Wt. (lbs.)
7640	1-3/8" to 2-7/8"	1/8"	24"	7/8"	10.6
7641	2-3/4" to 4-3/4"	1/8"	36"	1-1/8"	30.3



6969

Ratcheting Chain Wrench - 24"

- Ratcheting action makes it possible to re-grip without removing wrench.
- · Handles parts of most any shape... round, square, hexagon, or octagon.
- Handle is 24" long; chain grips objects ranging from 3" to 6-1/2" O.D.

516942 - Replacement chain



OTC Technician Gloves

- Washable synthetic leather palm with padding ensures comfort and a secure grip.
- Polyester and Lycra material around fingers offer a durable lightweight cover that stretches for a great fit.
- PVC cushions help protect knuckles from injury due to slippage.
- Comfortable polyester back panels include webbing for improved ventilation.

5800TGLV-M - Medium

5800TGLV-L - Large

5800TGLV-XL - Extra large

SmartTech™ Technician Gloves

· Same as above, also works with touchscreen technology.

5801SGLV-M - Medium

5801SGLV-L - Large

5801SGLV-XL - Extra large

6968

Ratcheting Chain Wrench - 12"

- · Works on many different-shaped objects, such as square, round, hexagon, oval, etc.
- Handle is 12" long; chain grips objects ranging from 1/2" to 4-1/2" O.D.

516941 - Replacement Chain



7400 **Ratcheting Chain Wrench**

This multi-purpose tool will grip parts of nearly any shape. It features a ratcheting head design that lets you turn in either direction without removing wrench from the work.

• 13" handle with capacity from 1/2" to 4-3/4" O.D.


209199 - Replacement Chain



Multipurpose Strap Wrench

You'll find many uses for this heavy-duty strap wrench. The 53" long nylon strap won't mar precision surfaces of shafts, pulleys, or other components. Useful on engine, transmission, and drive pulleys up to 16 inches. Special head design self-tightens the strap as force is applied to the lightweight, 12" long handle.

305085 - Replacement Strap



7640

7641

Heavy Duty Pulley Holder

This strap style universal wrench features a 9" drop forged handle and 23" leather strap for excellent grip on diameters up to 7". The milled foot increases gripon the strap and pulley as handle force is increased.



7401 **Ratcheting Chain Wrench**

This multi-purpose tool will grip parts of nearly any shape. It features a ratcheting head design that lets you turn in either direction without removing wrench from the work.

• 19" handle with capacity from 3" to 6-3/4" O.D.

209200 - Replacement Chain





RETAINING RING PLIERS

Here are a variety of retaining ring pliers, available individually or in sets, to handle many applications.

7053K

Internal/external retaining ring pliers kit. Includes four 90° tips (.038" diameter), four 45° tips (.047" diameter), and eight straight tips (.047" and .070" diameter).

Replacement tip kit. Contains 4 sets, 4 tips per set.

7123K

Convertible retaining ring pliers kit. For internal or external rings. Contains one No. 1120 (.038" diameter) and one No. 1340 (.070" diameter) straight tip pliers.



Convertible retaining ring pliers kit. For internal or external rings. Contains one No. 1125 (.038" diameter) and one No. 1345 (.070" diameter) 45° pliers.



Internal, straight tip retaining ring pliers. 16" long.

7301

External, straight tip retaining ring pliers. 16" long.





7300 Internal tip

Replacement tips (pairs):

209201 For pliers Nos. 7300 and 7301. 222029 45° for pliers Nos. 7300 and 7301. 222030 90° for pliers Nos. 7300 and 7301.



7301 External tip







INTERNAL **CONVERTIBLE EXTERNAL** No. 0100 No. 7300 No. 7301 No. 1120 No. 1340 No. 0200 No. 0300 No. 1125 No. 1345 No. 0400 No. 0500 No. 0600

How to select the correct pliers:

- 1. If ring number is known, locate ring number in chart —pliers are listed in right-hand column.
- 2. Or, measure diameter of shaft bore and locate size in chart—pliers are in right-hand column.

Ring	na column.	Bore of Shaft Dia.	
Series No.	Size Range (Ring Size No.	Range ("Inch" equiv.)	Pliers No.
	12 to 87	1/8" to 7/8"	0200
	12,15,25 to 66	1/8" to 21/32"	1120, 1125
	25 to 143	1/4" to 1-7/16"	7053K, 7123K, or 7125K
5100	93 to 143	15/16" to 1-7/16"	1340, 1345, or 0400
5100	31 to 75	5/16" to 3/4"	1340, 1343, 01 0400
5102 555	150 to 350	1-1/2" to 3-1/2"	0600
333	75	3/4"	0000
	354 to 650	3-35/64" to 6-1/2"	7301
	50 to 100	1/2" to 1"	0200
	50 to 78	1/2" to 25/32"	1120
	50 to 200	1/2" to 2"	7053K, 7123K, or 7125K
	106 to 200	1-1/16" to 2"	1340, 1345, or 0400
5108	215 to 334	2-1/8" to 3-11/32"	0600
	350 to 400	3-1/2" to 4"	7301
	37 to 102	3/8" to 1-1/32"	0100
	37 to 56	3/8" to 9/16"	1120, 1125
60	37 to 200	3/8" to 1-3/4"	7053K, 7123K, or 7125K
N5000 N5001	106 to 175	1-1/16" to 1-3/4"	1340, 0300
N5001	181 to 300	1-13/16" to 3-1/2"	0500
	306 to 625	3-1/16" to 6-1/4"	7300
	75 to 137	3/4" to 1-3/8"	0100
\bigcirc	75 to 100	3/4" to 1"	1120, 1125
	75 to 200	3/4" to 2"	7053K, 7123K, or 7125K
5008	143 to 200	1-7/16" to 2"	1340, 1345, or 0300
3000	206 to 300	2-1/16" to 3"	0500
	315 to 400	3-5/32" to 4"	7300

.038" tip diameter straight for removing internal rings.

0200

.038" tip diameter straight for removing external rings.

0300

.070" tip diameter straight for removing internal rings.

0400

.070" tip diameter straight for removing external rings.

0500

.090" tip diameter straight for removing internal rings.

0600

.090" tip diameter straight for removing external rings

7295

Retaining Ring Pliers

The "squeeze-lock" ratchet action of this tool locks retaining rings in position, making removal and installation easy. It features cushioned handles to ensure a secure grip

- · Will handle rings 3/16" thick and up to 4" in diameter.
- Pliers is 12" long

211051 Pair of replacement tips.

Retaining Ring Pliers

This tool removes the external retaining rings used in transmissions, differentials and other automotive components.

 Maximum spread is 1-1/16" and 7-3/4" long.

Horseshoe Lock Ring Pliers

This ruggedly built pliers is designed to spread and remove horseshoe lock rings used on hydraulic brakes, differentials.

transmissions, and CV joints.

• Handles are 8" long.



7412K

Retaining Ring Pliers Set

This set includes 12 of our most popular retaining ring pliers, in sizes for automotive applications. Tips include straight, 45°, and 90° angles in four different sizes (.038, .047, .070, and .090" diameter).

• Includes a sturdy plastic organizer box.



4512

Snap Ring Pliers Set - Internal/External

- For internal or external snap rings; thumbscrew permits quick conversion.
- Made of heavy-gauge tempered steel.
- Includes two stainless steel handled picks.
- Contained in a blow-molded plastic storage case.

Heavy-Duty Snap Ring Pliers Set (2 piece)

- Heat treated steel "circlip" pliers for large equipment repair.
- Replaceable tips and spring ratchet locking mechanism to securely hold against snap ring tension.
- Internal pliers' capacity 3-1/16" to 6-1/4" (78 mm to 159 mm)
- External pliers' capacity 3-1/2" to 6-1/2" (89 mm to 165 mm)
- Blow-molded storage case includes extra sets of replaceable
- Overall length 16"; handle length 12-1/2"

No. 4513 includes:

Tool No.	Description
4513-1	Internal snap ring pliers
4513-2	External snap ring pliers
4513-3	(2) .12" (3 mm) straight tip

Tool No.	Description		
4513-4	(2) .12" (3 mm) 45° tips		
4513-5	(2) .12" (3 mm) 90° tips		
4513-6	4 tip retaining screws		



7410

Retaining Ring Pliers with replaceable tips

An ideal tool for any transmission shop, this 13" long pliers with a maximum spread of 2.5" features replaceable tips and a spring-return handle.

214903

Set of replacement tips

No. 7412K Includes:

Description
.038" dia., straight
.038" dia., 45°
.038" dia., 90°
.047" dia., straight
.047" dia., 45°
.047" dia., 90°
.070" dia., straight
.070" dia., 45°
.070" dia., 90°
.090" dia., straight
.090" dia., 45°
.090" dia., 90°

All items can be purchased separately.

No. 4542 includes

No. 4512 includes:			
Tool No.	Description		
4512-1	.090" tip, straight pliers		
4512-2	.090" tip, 90° pliers		
4512-3	.070" tip, straight pliers		
4512-4	.070" tip, 90° pliers		
4512-5	.047" tip, straight pliers		
4512-6	.047" tip, 90° pliers		
4512-7	.038" tip, straight pliers		
4512-8	.038" tip, 90° pliers		
4512-9	straight tip pick		
4512-10	90° tip pick		

All items can be purchased separately.





Service S-ring and R-ring clips, internal or external, straight or angled. Ruggedly built of heat-treated chrome molybdenum steel.

- Set includes two internal snap ring pliers (one straight, one 45°) and two external snap right pliers (one straight, one 45°).
- All pliers have .038" (1.0mm) diameter tips
- Overall length 3"; handle length 2".









4509

Straight-Blade Hose Cutter

- Cuts rubber hoses ranging from 1/4" to 1-1/2".
- Simply place hose in tool and squeeze handle to
- Replacement steel cutter blade No. 4509-1 is

4509-1 - Replacement hose cutter blade.



4411

Ratcheting Hose & PVC Cutter (Standard)

- Cuts hose and PVC up to 1-3/8" dia.
- Features metal frame and ergonomic handles for high leverage.
- Compound ratcheting action provides maximum cutting power.
- Will also cut cable and wires.



Ratcheting Hose & PVC Cutter (Heavy Duty)

- Cuts hose and PVC up to 1-3/4" dia.
- Features metal frame and rubber padded ergonomic handles for high leverage and
- Compound ratcheting action provides maximum cutting power.
- Will also cut cable and wires.



Multi-purpose Scissors

Will cut hose, wire and cables, wood dowel, PVC, and thin sheet metals in addition to general cutting. The hardened stainless steel blades have an angle ground into one that eliminates slipping when cutting round materials.





5912

Crimpwell™ Angled Crimping Pliers

- Universal crimping design accommodates soft wire solid or stranded 10-22 AWG.
- · Cutting feature included for quicker preparation.
- 9" (228mm) in length, with protective grips to increase leverage and secure crimp.
- Angled design keeps the connector, the wire, and the crimper "in-line" –improving visibility and access in hard to reach places.
- Designed to not pierce connector insulation and also works on un-insulated connectors.
- Service tech can use as much force as desired to ensure connection and it will not damage connector insulation.
- Easy-to-use: Simply insert the connector into the crimping feature, slip over the connector and squeeze.



4510

Hose Pinch Off Pliers Set, 3 Piece

- Shuts off flow through vacuum lines, fuel lines, coolant lines, etc.
- Cocking ratchet mechanism holds pivoting jaws tightly in place. Heavy-duty swivel jaws pivot to assure parallel pinching.
- · Available separately:

4510-8 - 8" tool for small hoses and tight areas.

4510-10 - 10" tool for radiator and vacuum lines.

4510-12 - 12" tool for radiator and vacuum lines.



Universal Pulley Holder Locking Pliers

This adjustable locking pliers can be used to hold pulleys, clutch hubs, flywheels, gears, and sprockets with internal or external teeth up to a 4" diameter. Can also be used on applications with slots or holes with the 5/16" pins.



- Serrated jaws firmly grip the battery terminal nut or bolt
- Offset handles allow access in hard-toreach areas.
- Works on top-post and side-post battery terminals.



- Designed to remove and install relays, which are usually located in confined, hard-toreach areas.
- Specially coated tips offer a solid grip on the relay.

Cable Cutters, 1/4" & 3/8"

- Perfect choice for cutting heavier copper and aluminum cables.
- This tool is especially valuable for battery service where replacing a terminal is required.
- Clean cut with minimal mushing of wire strands.

4476 - 1/4" cable cutter. **4477** – 3/8" cable cutter.





Indexing Pry Bar Set, 3-Piece

- Sizes 10", 12" and 15".
- Indexible to 180° for better access.
- 14 locking positions for leverage in multipleapplications.
- Knurled handle assures a sure grip.
- Meets or exceeds ANSI specifications for pry bars

7172 - 10" Indexing Pry Bar 7173 - 12" Indexing Pry Bar 7174 - 15" Indexing Pry Bar



Heavy-duty pry bar made of tempered square steel that you can hit without damaging the handle

- Black chrome striking cap allows hitting the bar without damage to the handle.
- Ergonomic handle dual durometer composite handle for user comfort; reduces hand fatique.
- Polished tip with black oxide finish.
- Long-life finish resists rust and wear during use.
- OTC Marathon Lifetime Warranty.

8203 - 3-piece handled pry bar set in gray molded tray. Includes 12", 18", and 24" sizes.

8206 - 6-piece handled pry bar set in gray molded tray. Includes 8", 12", 18", 24", 32" and 36" sizes

8224 - 24" handled 8208 - 8" handled pry bar pry bar 8212 - 12" handled 8232 - 32" handled pry bar

8218 - 18" handled pry bar

8236 - 36" handled pry bar

Jimmy Bars

7171 **Pry Pac**

We've forged these bars from chrome alloy steel, then heat-treated them to resist bending and breaking.

7166 - 5/8" diameter, 18" long 7167 - 3/4" diameter, 24" long 7168 - 7/8" diameter, 30" long 7420 - 7/8" diameter, 46" long 7421 - 1" diameter, 54" long



You'll have a lot of leverage using one of these rolling head pry bars. The long, tapered body will also serve as an aligning drift.

7162 - Pry bar; 6" long 7163 - Pry bar; 12" long 7164 - Pry bar; 16" long 7165 - Pry bar; 18" long



Pry Bar Head

- Turns any 3/8" drive ratchet or breaker bar into a rolling head pry bar.
- Gives you the versatility of a pry bar without the storage problems.



9900A Persuader Pry Bar Merchansider

Three pry bars in one

 Heat-treated chrome alloy steel.

economical pack. You get 12"

and 18" rolling head pry bars and a 24" jimmy bar

The OTC 7168 Jimmy Bar features a forged chisel end for prying or lifting. This most popular model has a sharpened drift on the opposite end for alignment of heavy steel components for welding and fastening. The 7168 is the perfect choice for millwrights, rigging, demolition, aggregate mining and construction. Specially treated to resist bending or breaking, the OTC 7168 can "persuade" almost any obstacle encountered. Includes 10 Chisel and Alignment Jimmy Bars:

- 30" in length; 7/8" diameter.
- Forged and chromed alloy steel.
- Designed and heat-treated to resist bending and breaking.
- Made in USA.
- Lifetime warranty.

The sturdy cardboard merchandiser is 52" high, 18" wide and 12" deep, specifically designed for the Jimmy Bars, is free with purchase.



9901A MAJOR Persuaders Prv Bar Merchansider

The 9901A "MAJOR Persuader" merchandiser puts OTC's three biggest Jimmy Bars in a super convenient merchandiser designed to help increase in-store sales!

- Includes two 30" 7168 Jimmy Bars.
- Includes two 46" 7420 Jimmy Bars.
- Includes one 54" 7421 Jimmy Bar, covering almost any medium and heavy-duty application. The sturdy cardboard merchandiser is 64" high 16" wide and 18" deep, specifically designed for the Jimmy Bars, is easy to assemble and will safely hold up to five heavy-duty pry bars at one time.











EASILY REMOVE HOSES, CLIPS, WASHERS AND GASKETS

Short Pick, Long Pick and Hook Set, 14-piece

- Combines 8260, 8262 and 8263 sets.
- Packaged in molded trays which can be placed in tool drawer.



Short Pick and Hook Set, 4-piece

- · Consisting of four (4), 6.5", soft-handled picks.
- They are sturdy, with both stainless steel shafts and tips, with assorted tip shapes designed for marking, removing o-rings, accessing snap rings and other assorted applications.
- Ergonomic handle design fits properly in the hand, allowing for easier holding of the tool.
- Multi-use tools to scribe, align pierce, clean or remove o-rings, shaft seals, cv boot and motorcycle fork seals and dust hoods.
- Packaged in a molded tray which can be placed in tool drawer.



4508

Professional Style Seal Puller

- Designed to remove oil and grease seals when servicing cars, SUVs, and light trucks without damaging the housing or bearing.
- Hook tips in two sizes and professional handle design allows removal of hard-to-get-at seals by getting under them.
- The tool is 12" long and the hook tip is doublesecured (versus competitors' designs), for
- An extra blade is included, and additional replacements (No. 4508-1) may be ordered.

4508-1 - Replacement blade for 4508



Long Pick and Hook Set, 4-piece

- Consisting of four (4), 6.5", soft-handled picks.
- They are sturdy, with both stainless steel shafts and tips, with assorted tip shapes designed for marking, removing o-rings, accessing snap ring sand other assorted applications.
- Ergonomic handle design fits properly in the hand, allowing for easier holding of the tool.
- Multi-use tools to scribe, align pierce, clean or remove o-rings, shaft seals, cv boot and motorcycle fork seals and dust hoods.
- Packaged in a molded tray which can be placed in tool drawer.



8260

Hose Removal Set, 6-piece

- Consisting of six (6) hose removal tools which consists of three (3) 10", soft-handled tools and three (3) 15", soft-handled tools, each with a hard
- They are made of heat-treated, chrome steel with assorted tip shapes
- Ergonomic handle design fits properly in the hand, allowing for easier holding of the tool.
- Hose removal tools can also be used on upper and lower radiator hoses, clips, washers, gaskets and other items.
- Packaged in a molded tray which can be placed in tool drawer.



Fishing a stubborn o-ring or oil seal out of its seat is easy if you have this pair of picks in your toolbox.



O-Ring / Oil Seal Pick

Here's an extremely handy tool that makes quick work of oil seal and o-ring removal and installation.

4515

Mini Pick and Hook Set, 4-piece

- Sturdy stainless steel points and shafts designed for marking, removing o-rings, accessing snap rings, and performing other tasks. Assorted angle tips allow you to reach awkward locations.
- Knurled shaft design enhances finger control for delicate jobs.



Windshield Spray Nozzle Needle

- Makes quick work of clearing obstructions from the windshield washer spray nozzle.
- Easily pierces corrosion or remove blockage.
- The barrel is knurled for grip and control.
- Threaded end caps keep the needle points covered when not in use. The pocket clip keeps the tool handy.



Brass Punch Set (2 piece)

- Two large, brass non-sparking punches. Ideal for use near precision parts or in locations where sparks from ferrous metal could be hazardous.
- Includes an 8" punch (5/8" hex, tapered to 3/8") and 10" straight punch (3/4" dia., chamfered at both ends).



4606

Brass Hammer and Punch Set

- Brass-head hammer and punches are ideal to use where sparks from ferrous metals would be hazardous, or where precision metal parts could be damaged by steel tools.
- Hammer head weighs 24 oz.; brass drift punch is 10" x 3/4" diameter; brass tapered punch is 8" x 5/8" hex tapered to 3/8' diameter point.







OTC BFH HAMMER LINE

OTC No.	Head Weight	Handle Length	Total Weight	
Double Face Sled	ge Hammer, Ind	estructible Hand	le	
5790ID-616	6 lbs.	16"	7.6 lbs.	
5790ID-624	6 lbs.	24"	9.4 lbs.	
5790ID-630	6 lbs.	30"	10.4 lbs.	
5790ID-812	8 lbs.	12"	8.9 lbs.	
5790ID-816	8 lbs.	16"	9.7 lbs.	
5790ID-824	8 lbs.	24"	11.2 lbs.	
5790ID-830	8 lbs.	30"	12.4 lbs.	
5790ID-1030	10 lbs.	30"	14.0 lbs.	
5790ID-1230	12 lbs.	30"	16.6 lbs.	
5790ID-1430	14 lbs.	30"	18.5 lbs.	
Club/Hand Drill Hammer, Indestructible Handle				
5791ID-312	2.5 lbs.	12"	4.0 lbs.	
5791ID-412	4 lbs.	12"	5.1 lbs.	
5791ID-416	4 lbs.	16"	5.5 lbs.	
Cross Peen Hammer, Indestructible Handle				
5792ID-216	2 lbs.	16"	4.5 lbs.	
5792ID-316	3 lbs.	16"	5.4 lbs.	
Ball Peen Hammer, Indestructible Handle				
5793ID-2414	24 oz.	14"	2.6 lbs.	
5793ID-3214	32 oz.	14"	3.0 lbs.	
Tire Service Hammer, Indestructible Handle				
5789ID-1032	10 lbs.	32"	14.4 lbs.	
5789ID-520	5 lbs.	20"	7.3 lbs.	



BFH Hammer

- Indestructible handle never needs replacement
- Ergonomic rubber grip handle reinforced with steel bars resists breaking while absorbing impact and vibration
- Drop-forged head is induction-hardened for long life, and contains steel locking plates that are specially bonded to ensure the head never becomes loose.
- Tire Service Features for 5789ID-1032 and 5789ID-520.
- Use top hook as a wheel tipper; sledge end hook to drag tire into position.
- Bead breaking wedge has grooves and a convex shape to help drive tire lube into the bead.





Brass Hammer and Punch Set


- Brass-head hammer and punches are ideal to use where sparks from ferrous metals would be hazardous, or where precision metal parts could be damaged by steel tools.
- Two hammer head weighing 24 and 12 oz.
- Two tapered punches 14" x 5/8", 10" x 5/8".
- One hex tapered punch 8" x 5/8"
- Two drift punches 10" x 3/4", 8" x 1/2".
- Two pin punches 6" x 3/8", 4" x 1/4".



Master Bushing Drive Set (33 piece Metric & Standard)

- Enables you to remove and install bushings ranging from 10mm to 42mm in diameter, and 3/8" to 1-3/8" in diameter, as used import cars, trucks, tractors, construction equipment, electric motors, and many other components having bushings.
- Includes large, medium, and small driver handles and adapters all made of steel.
- · Housed in a blow-molded storage case.

6939 **Broken Bolt Extractor Tool**



• Can also be used to remove and install wheel studs and other general pressing needs.

6939-1 **Broken Bolt Extractor Adapter Set**

the 7248 C-Frame.

Available for use with

7248 **C-Frame Press**

 Used for removing/ installing; universal joints with needle bearings, pressed in wheel studs, and brake anchor pins on heady-duty vehicles. Suitable for general pressing operations





26



4605

Interchangeable Punch and Chisel Set

• Safety protective handle allows easy grip and protects hand from being hit by hammer.

12 punches and chisels included: 5 flat chisels: 1/2", 5/8", 3/4", 7/8", and 1" wide blades 1 cape chisel: 1/4" wide blade 2 taper punches: 1/8" and 1/4" diameter 2 pin punches: 3/16" and 1/4" diameter 2 center punches: 1/8" and 3/16"

 Double locking ball detent holds punch or chisel securely in the driver handle. Replacement parts available:

4605-1 — Drive handle	4605-8 — 1/8" taper punch
4605-2 — 1/2" wide flat chisel	4605-9 — 1/4" taper punch
4605-3 — 5/8" wide flat chisel	4605-10 — 3/16" pin punch
4605-4 — 3/4" wide flat chisel	4605-11 — 1/4" pin punch
4605-5 — 7/8" wide flat chisel	4605-12 - 1/8" center punch
$ \begin{tabular}{ll} \bf 4605-6 - 1" \ wide \ flat \\ \it chisel \end{tabular} $	4605-13 — 3/16" center punch



Impact Drivers

4605-7 - 1/4" cape

chisel

- Loosens hard-to-turn screws, bolts or nuts.
- Handle design prevents possibility of hitting hand with hammer when striking impact driver.
- Bit holder has 3/8" drive (No. 4608), 1/2" (No. 4607) drive, and 5/16" hex for Phillips and flat screwdriver bits.

- 5/16" wide x 1-3/8"

- 5/16" wide x 3-1/8"

long with 5/16" hex

long with 5/16" hex

- 3/8" wide x 3-1/8"

long with 5/16" hex

slotted bit

slotted bit - 3/8" wide x 1-3/8"

slotted bit

slotted bit

long with 5/16" hex

- · Includes eight screwdriver bits:
- No. 2 Phillips bit. 1-3/8" long with 5/16" hex
- No. 2 Phillips bit, 3-1/8" long with 5/16" hex
- No. 3 Phillips bit, 1-3/8" long with 5/16" hex
- No. 3 Phillips bit, 3-1/8" long with 5/16" hex
- 4607 1/2" Impact Driver.
- 4608 3/8" Impact Driver.



Bearing Race and Seal Driver Kit

- The Bearing Race and Seal Driver Kit provides a convenient way to smoothly and quickly position a bearing in the inner hole of an axle.
- The kit includes a handle grip and six heavyduty bearing drivers. The drivers have different diameters in order to match different-sized bearings, and three of the drivers are formed with two different diameters.
- Bearing Driver Sizes:

1.555" (39.5 mm) 1.752" (44.5 mm) 1.968" (50.0 mm) 2.322" (59.0 mm) 2.48" (63.0 mm) 2.559" (65.0 mm) 2.834" (72.0 mm) 2.992" (76.0 mm) 3.189" (81.0 mm)



4505

Bushing Driver Set, 19 piece

- Enables you to remove and install bushings ranging from 3/8" to 1-3/8" in diameter, as used in cars, trucks, tractors, construction equipment, electric motors, & many other components having bushings.
- Includes: Large, medium, and small driver handles with nuts; sixteen bushing adapters ranging from 3/8" to 1-3/8".
- Housed in a blow-molded storage case.



Metric Bushing Driver Set

- 14-piece tool kit for motorcycles, Asian and European vehicles contains adapters: 10-12 mm, 14-16 mm, 15-17 mm, 16-18 mm, 18-20 mm, 20-22 mm, 22-24 mm, 25-27 mm, 28-30 mm, 30-34 mm, 32-36 mm, 35-40 mm, 38-42 mm; one small driver handle; one medium driver handle; one large driver handle.
- Aluminum construction won't mar the bushing. or affect bushing tolerance, which is critical for efficient operation of the engine, transmission, and hubs



4507 Bearing Race and Seal Driver Set, 10 piece

- This aluminum constructed set permits installation of tapered bearing races and seals without damage to the component or housing
- Tapered side of driver is used to install races. Invert the driver to the flat side to install seals.
- Set is housed in a blow-molded plastic
- Includes driver handle with bolt, plus these tool sizes: 1.565", 1.750", 1.965", 2.325", 2.470", 2.555", 2.830", 2.995", and 3.180".



13

14

9 10 11 12

- Punch and Chisel Set, 16 piece • Durable set of heat-treated chrome vanadium steel punches and chisels. Storage tray included.
- 3 Cold chisels (with gauge): 3/8" x 5-1/2"; 1/2" x 6": 5/8" x 6-1/2"
- 2 Center punches: 1/8" x 5": 3/16" x 6"
- 5 Pin punches: 3/32" x 4-1/4"; 1/8" x 4-3/4"; 5/32" x 5"; 3/16" x 5-1/4"; 1/4" x 5-3/4"
- 5 Taper punches: 3/32" x 5-1/4"; 1/8" x 5-3/4"; 5/32" x 6"; 3/16" x 6-1/4"; 1/4" x 6-3/4"
- 1 Chisel gauge

Available separately			
No.	Part No.	Description	
1	4600-15	Taper Punch, 1/4" x 6-3/4"	
2	4600-14	Taper Punch, 3/16" x 6-1/4"	
3	4600-13	Taper Punch, 5/32" x 6"	
4	4600-3	Cold Chisel, 3/8" x 5-1/2"	
5	4600-2	Cold Chisel, 1/2" x 6"	
6	4600-1	Cold Chisel, 5/8" x 6-1/2"	
7	4600-4	Center Punch, 3/16" x 8"	
8	4600-5	Center Punch, 1/8" x 5"	
9	4600-12	Taper Punch, 1/8" x 5-3/4"	
10	4600-11	Taper Punch, 3/32" x 5-1/4"	
11	4600-10	Pin Punch, 3/32" x 4-1/4"	
12	4600-9	Pin Punch, 1/8" x 4-3/4"	
13	4600-8	Pin Punch, 5/32" x 5"	
14	4600-7	Pin Punch, 3/16" x 5-1/4"	
15	4600-6	Pin Punch, 1/4" x 5-3/4"	
16	4600-16	Chisel Gauge	



BODY SERVICE NUMERICAL INDEX

0100	2529RA2	4512-4	4605-12 27	5790ID-143026
020022	2529RH2	4512-5	4605-1327	5791ID-312 13, 26
030022	2531	4512-6	4606	5791ID-412 13, 26
040022	2531RB3	4512-7	4607	5791ID-416 13, 26
050022	2534	4512-8	460818, 27	5792ID-216
060022	2535	4512-9	4613	5792ID-316
714	2535RB	4512-10	4614	5793ID-2414
898A9	2537	4513	4616	5793ID-3214
1120	2537RB3	4513-2	4629 8, 26	5800TGLV-L
112522	2541	4513-3	4651 8, 17	5800TGLV-M20 5800TGLV-XL20
113122	2541-1	4513-4	4658 7, 25	5801SGLV-L20
115511	2541-2	4513-5	4676	5801SGLV-M
1156	2541-3 3	4513-6	4676PN12	5801SGLV-XL20
1320	2541-3 3	4514	4705 8	5900A 9, 15
1325	2541-4	4515	4706	590516
1329	2541-4	45468	471112	5905-816
1340	2543	4546-18	4712	5905-1016
1345	2543-1	4546-28	4715	5905-15
1349	2543-23	45496	4715-112	5905-2016
1513B	2543-33	4549-16	4715-2	5905-2516
1515B	2543-4	4549-26	4715-3	5905-2716
1517A	4082A10	4549-36	4715-4	5905-3016
1519A	4083B10	4550	4715-5	5905-4016
1565	4085	4554	4715-7	5905-45
1569	440727	4576	4715-8	5905-5516
2470 5	440827	460027	4715-9	5906
2471 5	4410	4600-127	4784	590815
2472 5	4411	4600-227	4791	5912
2473 5	4412 9, 23	4600-327	4792	5918
2474 5	44487	4600-427	480223	5919
2475 5	44497	4600-527	480420	5920
2476 5	4450	4600-627	4818	5921
2477 5	4452	4600-727	5073	5922
2478 5	4467	4600-827	5074	5923
2479 4	4468	4600-927	508614	5924
2480	4476	4600-1027	5550 5	5925
2481	4477	4600-1127	5551 5	5926
2482	44858 44896	4600-12	5552	5927
2484 4	44926	4600-1327	5776-1	5929
2485 4	449323	4600-1527	5776-2	5930
2487	450527	4600-1627	5776-3	5931
24884	4507	4602	5776-4	5931-6
2489-84	450825	460527	5776-5	5931-7
24904	4508-125	4605-127	5789ID-52026	5931-8
2491 4	4509 9, 23	4605-227	5789ID-103226	5931-10
2492 4	4509-19, 23	4605-327	5790ID-61626	5931-1116
2524 2	4510	4605-427	5790ID-62426	5931-12
2525 2	4510-823	4605-527	5790ID-63026	5931-14
2525RB2	4510-10	4605-627	5790ID-812	5931-16
2526	4510-12	4605-727	5790ID-81626	5934
2527	4512	4605-827	5790ID-82426	5935
2527RA	4512-122	4605-927	5790ID-83026	5936
2528	4512-222	4605-1027	5790ID-103026	
2529 2	4512-3	4605-11	5790ID-1230 26	



5937	6181	6956-616	7324	8218
5938	6182	6956-716	7325	8224
5939	6183 15, 16	6956-816	7326	8232
594017	6184	6956-916	7327	8236
5942	6185	6956-1016	7328	8260
5942-4	6186	6958	7329	8260M
5942-5	6187	6958-1	7330	8262
5942-816	6191	6958-316	7332	9101B
5942-1016	6192	6958-4	7333	91018
5942-12	6193	6958-516	7334	9104B10
5942-14	6198	6958-616	7345	9110B
5942-16	6627	6958-716	7346	9900A24
5945	66426	6958-816	7347	9901A24
5950A13	6676	6958-916	7348	14450
5950S13	6785 6	6958-1016	7349 17	15702 21
602217	6939	696820	7350	184039
6100	6939-1	696920	7351	4499711
6101	6950	698617	7352	202817
6102	6950-116	6986-117	7353	2053789
6103	6950-216	6986-217	7354	20680318
6104	6950-316	6986-317	7355	20919920
6105	6950-416	6986-4	7356	20920020
6107	6950-5	6987-617	7358	209201
6108	6950-716	6987-817	7359	214903
6109	6950-816	6987-10	7360	21688418
6110	6950-916	6987-12	7365	22202921
611115	6950-1016	7053K 21	7367	22203021
6112	6952	7103 25	7368	30508520
6135	6952-1	7123K 21	7375	50488814
6145	6952-216	7125К 21	7377	50488914
6150	6952-3	7162	7378	516941 20
6151	6952-416	7163	7379	516942 20
6152	6952-516	7164	7380	5392547
6153	6952-616	7165	7380	5392557
6154	6952-7	7166	7400	5392567 5574799
6156	6952-9	7168	7401	5574809
6157	6952-10	717124	7410	5577009
6160	6954	717211, 24	7412K	
6161	6954-116	717311, 24	7415	
6162	6954-216	7174	7420	
6163	6954-316	7175	7421 24	
6164	6954-416	7206	7575	
6165	6954-516	7248	7640 20	
6166	6954-616	7295	7641	
6167	6954-716	7300 21	7687A24	
6170	6954-816	7301	7703	
617116	6954-916	7307	7827	
6172	6954-10	7308	7955	
6173	6956	7312	7956	
6175	6956-2	7313	820311, 24	
6176	6956-316	7321	8206	
6177	6956-416	7322	8208	
6180	6956-516	7323	8212	

BODY SERVICE ALPHABETICAL INDEX

Accutorg™ Clikker Torque Wrenches 19	Heavy Duty Pulley Holder	Ratcheting Hose and
Adjustable Hook Spanner Wrenches 18	Heavy-Duty Snap Ring Pliers Set, 2 piece22	PVC Cutter (Standard) 9, 23
Air Bag Release Tool Kit	Heel Dolly Block	Retaining Ring Pliers
Air Wedge Lockout Tool	Hex Key Wrenches	Rolling Head Pry Bars
Angle-Tip Relay Pliers	Hole Punch Kit 8	Rolling Head Pry Bars24
Automatic Wire Stripper	Horseshoe Lock Ring Pliers	Round Body Anvil
Basic Slide Hammer Units	Hose Pinch Off Pliers Set, 3 piece 23	SAE Ball Hex "L" Keys
Battery Pliers	Hose Removal Set, 6-piece	1/16" to 3/8", 10-piece
Battery Terminal Wrench, 10mm	Hydraulic Rams for Collision Repair Sets 10	Saturn Window Glass Socket 6
Bearing Race and Seal Driver Kit	Hydraulic Spreaders	Screw Extractor Set
BFH Hammer	Impact Drivers	Self Adjusting Wire Stripper, 9"
Blind Panel Removal Wedge	•	, , ,
	Indexing Pry Bar Set, 3-piece	Short Pick and Hook Set, 4-piece 12, 25 Shrinking Hammer
BMW Head Bolt Socket	Interchangeable Punch and Chisel Set 27	3
Body and Fender Dent Puller	Jimmy Bars	Side Terminal Battery Wrench
Brass Hammer and Punch Set 8, 25, 26	Light Dinging Spoon	Single Spotweld Carbide Drill Bit 4
Brass Punch Set, 2 piece 8, 25	Lockout Tool Set, 6-piece	Slide Hammer Puller, Ten-Pound
Broken Bolt Extractor Tool	Long Pick and Hook Set, 4-piece 12, 25	SmartTech™ Technician Gloves20
Bumping Tool Set, 3-Piece	Long-Side Terminal Battery Wrench 18	Snap Ring Pliers Set – Internal/External 22
Bushing Driver Sets	MAJOR Persuaders Pry Bar Merchansider 24	Spanner Wrenches
C-Frame Press	Master Lockout Tool Set	Spot Weld Breaker
Cable Cutters, 1/4" & 3/8"	Master TORX® Socket Set 9, 15	Spotweld Carbide Drill Bit Set, 5-piece 4
Collision Repair Sets	Metric Ball Hex "L" Keys	Spot Weld Cutter Set
Combination Wedge Pry Tool 4	1.5mm to 10mm, 10-piece 16	Standard TORX® Socket Set 15
CrimPro™ 4-in-1 Angled Wire Tool 13	Metric Bushing Driver Set 27	Steering Wheel Holder
CrimPro™ 4-in-1 Wire Tool	Metric Hex Key Wrench Set 17	and Pedal Depressor Kit
Crimpwell™ Angled Crimping Pliers 13, 23	Metric Hex Socket Set, 7-piece 16	Stepped Lever Wedge 4
Cross Chisel Curved Hammer 3	Mini Pick and Hook Set, 4-piece 12, 25	Straight-Blade Hose Cutter
Curved and Flat Dolly 5	Mini Snap Ring Pliers Set, 4-piece 22	Stud Remover Set, Fractional/Metric 17
Deluxe European Radio Tool Set 12	Multi-purpose Scissors 9, 23	Telescopic Support8
Deluxe Radio and Antenna Service Kit 12	Multipurpose Strap Wrench 20	Toe Dolly Block
Dial Torque Wrench	O-Ring / Oil Seal Pick Sets 25	Torque Angle Gauge
Door Buzzer Shutoff Tool	OTC Technician Gloves 20	Torque Multipliers
Door Panel & Upholstery Tool Set 6	Persuader Pry Bar Merchansider 24	Toyota Head Bolt Socket
E-Clip Tool Set, 5-Piece	Pick Hammers4	Trim & Bezel Tool 5
Edge Straightener5	Pinch Seam Straightener 4	Trim Fastener and Molding Removal Set 6
Euro Door Handle Kit	Power Door Skin Remover 2	Trim Tool Kit, 11-piece 6
Euro Radio Removal Tool Kit 12	Power Door Skin Remover Air 2	Trim Wedge, 30mm and 60mm 4
Extended Reach Bumping Tool 5	Power Hemming Tool 2	Truck Windshield Wiper Puller, 18mm 7
External Torx® Plus Socket Set (8-piece) 16	Power Hemming Tool Air 2	Universal Brake Caliper Socket Set 15
Finishing Hammer, 160mm x 40mm 4	Power Quarter Panel Hemming Tool 2	Universal C-Frame Nut Splitter
Fin Straightener9	Power Quarter Panel Hemming Tool Air 2	Universal Hook
Ford Air Bag Simulator	Power Shear 16	Universal Lift Support Clamp
Ford Mirror Removal Tool 6	Power Shear 16 Air	Universal Outside Thread Chaser
Ford Radio Removal Tool Kit	Power Shear 18 3	Universal Pulley Holder Locking Pliers 23
Fraction Hex Socket Set (7-piece) 16	Power Shear 18 Air	Utility Pick Hammer
General Purpose Dolly	Power Shear Corrugated Metal	Window Trim and Molding Remover5
General purpose Pick Hammer	Preset Torque Wrenches	Windshield Spray Nozzle Needle 7, 25
Giant Adjustable Wrenches	Professional Scraper Set, 3-Piece 6	Windshield Wiper Puller
Grip Wrench Adapters	Professional Style Seal Puller	Windshield Wiper Puller and
Half Round Bumping Tool. 5	Profile Gauge, 10" 9	Nozzle Needle Combo
Hammer & Dolly Sets	Pry Bar Head	Work Lights
Handled Pry Bars	Pry Pac	work Lights
Heat Gun	Punch and Chisel Set, 16 piece	
Heavy-Duty Adjustable	Ratcheting Chain Wrench	
HookSpanner Wrench	Ratcheting Hose and	
Heavy Duty Profile Straightening Tool 5	PVC Cutter (Heavy Duty) 9, 23	





BOSCH AUTOMOTIVE SERVICE SOLUTIONS INC. 28635 MOUND ROAD WARREN, MI 48092 USA

TECH SERVICES

PHONE 800 533 6127 FAX 800 955 8329 CUSTOMER SERVICE PHONE 800 533 6127 FAX 800 283 8665

www.otctools.com

15-143 © 2015 Bosch Automotive Service Solutions Inc.