

GET AN EXTRA HAND UNDERNEATH

UNDERHOIST AND SUPPLEMENTARY STANDS WITH A LIMITED LIFETIME WARRANTY

OTC UNDERHOIST STANDS

UH15

1,500-lb capacity underhoist stand

- Threaded rod for easy adjustment lowering and raising to work height
- 11-7/8" flat round base makes full ground contact for stability
- Freestanding support stand aids in R&I of transmissions, radiators, driveshafts, exhaust systems and more
- Not intended to stabilize or support vehicles

UH15FP

1,500-lb capacity underhoist stand with foot pedal

- Foot pedal provides hands-free adjustment and quickly raises saddle to work height
- 11-7/8" flat round base makes full ground contact for stability
- Freestanding support stand aids in R&I of transmissions, radiators, driveshafts, exhaust systems and more
- Not intended to stabilize or support vehicles

UH20

4,000-lb capacity high reach supplementary stand

- Designed to stabilize vehicles when lifted on hoists
- Extra-sturdy tripod base prevents tipping and leaning
- Secure support column and speed screw for quick adjustment and reliable holding



UH15

UH15FP

UH20

Spec	UH15	UH15FP	UH20
Capacity	1,500 lbs	1,500 lbs	2,000 lbs
Max. Height	80.75"	80.75"	85"
Min. Height	54.25"	54.25"	56-1/4"
Footprint	11-7/8" flat round	11-7/8" flat round	24" triangular tripod base
Adjustment	Threaded rod with T-handle	Foot pedal assist and threaded rod with T-handle	Threaded rod with T-handle
Saddle	5-1/4" x 1-1/4" U-shape	5-1/4" x 1-1/4" U-shape	3-3/16" x 3-3/16" square
Safety	Tested to meet all ASME PASE-2019 safety standards	Tested to meet all ASME PASE-2019 safety standards	Tested to meet all ASME PASE-2019 safety standards

2006_1041