

PROMOTIONS

All promotions valid 7/1/2021 - 12/31/2021, unless otherwise stated. Some restrictions may apply. For promotion details and to redeem, visit Boschrebates.com. Dated proof of purchase and/or serial number(s) required when registering for rebate. Must redeem within 30 days of promotion end date.

Try a Bosch ADS or ADS X, risk-free Bosch ADS 30-day money back guarantee

If you are not satisfied with your new Bosch ADS tool, return it back to Bosch for a refund.*



*For more information about the 30-day money back guarantee, call 1-855-BOSCHTECH (1-855-267-2483) or visit boschdiagnostics.com/promotion/risk-free-ads

Bosch ADS X Limited Time Promotion



Purchase and register an ADS 525X, receive choice of a free Circuit Analysis Tool or Battery System Tester



(SKU 3920) (SKU 1699501320)

Purchase and register an ADS 625X, receive choice of a free TPMS Tool, Circuit Analysis Tool or Battery System Tester



TPA 300 VET 100 BAT 120 (SKU 3934) (SKU 3920) (SKU 1699501320)

Must-have A/C accessories



LD7 – Premium refrigerant leak detector LD9-TGKIT – Tracer gas leak detector service kit

41234 – R1234yf aluminum manifolds and hose set

EVDC100 – Electronic variable compressor tester

Sure, calibrate with a tape measure.

Just try not to scrape your knuckles on the ground in the process.

The superior and highly evolved ADAS workflow can guide you from setup through calibration in half the time.





Uncover the truth about the superior solution at boschdiagnostics.com/adas

ALL-NEW ADS X

Turn your diagnostic powers into superpowers.

Go from technician to superhuman diagnostic machine with your new secret weapon. Just remember, with great power comes great diagnosability.



Extreme speed

- All-system scans on average under 60 seconds
- Redesigned wireless
 VCI for faster, more
 efficient diagnosing

Extreme flexibility

- Battery life for days
- Modular software subscriptions for what you need most

Extreme access

- 100% OE-approved for security gateway
- Industry-leading vehicle coverage back to 1976

Uncover the truth about the all-powerful X **boschdiagnostics.com/ads-x**



MUSCLETOOLS Bosch Diagnostics

Unbeatable coverage for HD trucks, construction equipment and more



Windows 10 Touchscreen tablet

New & Improved



NEW

Increase Shop Efficiency with the Bosch ESI[truck]

DPF regeneration, component actuation, special tests and automatic module identification for Class 4-8 trucks and more.

3824A

Truck, engine, and system coverage

- Truck brands: Freightliner, International, Kenworth, Mack, Volvo, Peterbilt, Sterling, Western Star, and more
- Engine brands: PACCAR, Perkins, Detroit Diesel-MBE, Mack, Navistar, Caterpillar, Deutz, MTU, and more
- System coverage: transmissions, brake systems, trailer ABS, exhaust treatment, and more

Expert-level diagnostics

- Automatic vehicle ID
- ▶ Fault code reading, reporting, clearing
- Diesel particulate filter (DPF) regeneration
- Cylinder cut-out
- ► Injector coding and trim files
- Key component actuations
- Special tests
- Vehicle parameter modifications

3824A-TBL

Heavy Duty Tablet Upgrade

- Everything you need to upgrade an existing 3824 ESI[truck] Tablet to the new and improved 3824A model.
- Windows 10 Touchscreen tablet



3824-08R

Troubleshooting & Repair Subscription

- ► Faster, more efficient heavy duty vehicle repairs
- 13,000+ procedures guide user through each step to troubleshoot vehicle issues
- Procedures by DTCs or by vehicle symptoms
- ► Technical Service Bulletins (TSBs) included

ESI[truck] Off-Highway Upgrade Cable Kit with Introductory Software License (3824CBL-UPG)

Add off-highway vehicle and machinery coverage for multiple manufacturers to your 3824 or 3824A ESI[truck] scan tool. Coverage included for:

- Construction equipment
- Agricultural vehicles
- Stationary engines
- Street sweepers and more
- Manufacturer coverage: Caterpillar, John Deere, Kubota, Perkins, Volvo, Massey Ferguson, SISU, Deutz, Deutz-Fahr, MTU, and more
- System coverage: Gearbox, HVAC, engine, steering, hydraulic systems, suspension, electronic modules, antipollution, central computer and more
- Diagnostic coverage: Manual processes, diagnosis info, measurable values, component actuations, ECU data, parameter IDs (PIDs), calibrations and resets, system technical data, wiring diagrams, vehicle technical data and vehicle maintenance info

3824CBL-UPG

Kit contents:

- ► 10 cables for machinery, construction equipment, agricultural vehicles and more
- ESI[truck] off-highway software package with full diagnostic capabilities. Introductory off-highway software expires when your ESI[truck] heavy duty truck software expires
- Software renewals can be done simultaneously, ensuring continuous HD truck and off-highway vehicle coverage

3824-08OHW

ESI[truck] Off-Highway 1-Year Software License

- 12-months of off-highway diagnostic coverage, including all coverage updates
- Used to renew initial software included with Offhighway upgrade cable kit with introductory software license

3824-08

ESI[truck] 1-Year Renewal License

 1-Year (12-month) renerwal license for existing ESI[truck] user.

BAT155

Heavy Duty Battery and Electrical System Analyzer

The BAT 155 is an advanced heavy duty battery & electrical system tester designed for the commercial vehicle industry. Featuring patented single load, dynamic resistance technology that provides fast and accurate results.



Ask your tool dealer about adding off-highway vehicle coverage to your ESI[truck]





For more information on software updates and off-highway coverage upgrades, visit boschdiagnostics.com

Off-highway cable upgrade kit and off-highway software only compatible with 3824A, 3824 and 3824BSC ESI[truck] diagnostic tools. Customer must first purchase Offhighway upgrade cable kit with introductory software (3824CBL-UPG) prior to purchasing or activating Off-highway 1-year software license (3824-080HW)

MUSCLETOOLS Bosch Diagnostics

3920 VET 100 Circuit Analysis Tool

Quickly identify electrical issues in failed circuits

Bosch VET 100 Circuit Analysis Tool

- Perfect tool for Data stream analysis using vour scan tool
- Identify failed circuit component, wiring or PCM
- Simulates the sensor you are diagnosing by inputting a determined voltage at the sensor location
- Allows input voltage from .5VDC -7VDC in .5VDC increments
- Use your scan tool to verify if correct voltage is being applied to circuit
- Bypass sensor to send desired voltage back to PCM

Works on computer controlled components including:

- Camshaft sensors and Crankshaft sensors
- Throttle body sensors
- ▶ MAF sensors and MAP Sensors
- Temperature sensors
- Parking sensors
- ADAS sensors
- Oil pressure sensors
- Transducer based components
- ▶ EGR signal voltage up to 5VDC
- ► Acc pedal voltage up to 5VDC
- Works with 12V and 24V systems with vehicle voltage displayed. Also includes a "flashing" low battery voltage indicator

TPA 300 Grow your aftermarket solution with complete TPMS sensor coverage





3920

Pair with any Bosch diagnostic tool to program new sensor IDs via OBD

- Activate and read TPMS sensor data. program sensors, check remote keyless entry signal and display sensor data in seconds
- ▶ Perform OBD II relearns within minutes when paired with a compatible Bosch manufactured diagnostic scan tool
- Full database of indirect, manual and auto relearn procedures
- ▶ Intuitive, full-color display with easy vehicle lookup by make, model and year
- Supports all known OE and aftermarket programmable sensors for all light vehicles
- New features, vehicles and sensor coverage added regularly
- Includes 3 years of free software updates

Compatible with any Bosch manufactured diagnostic tool

DAS 3000-1

ADAS Recalibration System

A complete ADAS recalibration package that enables shops to quickly, easily and precisely recalibrate Automated Driver Assist System



HDS 250 Heavy-Duty Scan Tool for Class 4-8 Vehicles

Ideal for heavy-duty shops as a second diagnostic tool and mobile repair trucks. **Cost-effective solution for aftermarket** shops in need of heavy-duty coverage HDS 250 Features

- Brilliant Color Display
- Rugged enclosure for durability
- Class 4 Class 8 truck coverage featuring "Automatic Protocol Search"
- ▶ HD J1587 / J1708 and J1939 CAN, Engine, Transmission/ABS coverage and more
- Global OBD II Quick Test
- Works on 12V and 24V systems
- Gasoline and diesel engine coverage
- Read and clear diagnostic trouble codes
- Live vehicle data includes
- Engine speed
- Engine ECU temperature - Percent acceleration pedal position
- Engine intercooler temperature
- Engine coolant temperature
- Battery voltage
- Alternator voltage output
- Ambient air temperature
- Air inlet temperature
- On-screen definitions of diagnostic trouble codes

HDS 250 Includes

HD Scan tool, 9 Pin Deutsch Cable, 6 Pin Deutsch Cable, 16 Pin HD/ OBD II Cable, USB Cable, Quick Start Guide, Carrying Case and 1-Year Warranty.



1699200240





KOBINAIR



Trusted Robinair platform, new features

Introducing the new AC1234-4SL and 34988NI-SL machines with integrated scale lock

The mechanical scale lock protects the scale during transport for mobile or agricultural service.

Special tie-down points and guidelines ensure your machine is safe and secure for mobile service.

Both machines feature legendary Robinair guality, the largest nationwide support and service network, automatic oil drain and patented automatic internal tank refill for more efficient service.





34988NI-SL

Built-in WiFi, Bluetooth and Android OS

34998 Connected R-134a RRR machine

- Meets or exceeds SAE J2788 standards for R-134a recovery
- > Two oil inject bottles; one dye inject bottle

AC1234-9 Connected R-1234yf RRR machine

- Meets or exceeds SAE J2843 standards for R-1234yf recovery
- Integrated refrigerant analyzer protects machine and vehicle system

Both machines feature:

- > Industry-leading 10.5" hi-res touch screen with easy-to-use controls
- > Wi-Fi® and Bluetooth® connectivity for wireless accessories and performance enhancements
- Legendary Robinair quality, field and service support
- Made in Owatonna, Minnesota, USA with global components
- > Built-in training videos and speaker with web access for more training and A/C service info
- ACS-250 wireless VCI and 80212 Bluetooth temp probe compatible
- Includes wireless software updates and refrigerant capacity database access*
- > Mopria Print Service wireless printing with report export option for customers or insurance companies

* Annual purchase of refrigerant capacity database software card or Product Authorization Code (PAC) code required to download new capacity database



MUSCLETOOLS Robinair A/C Tools & Equipment

What wireless accessories fit my machine?

A/C Machine	A/C Capacities DB	Cover	Printer
34788, 34788-H, 34988	34411-L	17492	34988 only
34288NI, 34788NI, 34788NI-H	34412-F	17499	30038
34988NI	34412-F	17499	Included
34998	34001	17499	Mopria Print Service wireless printing
AC1234-4	34413-D	17499	30038
AC1234-6	34414-B	17499	Included
AC1234-9	34002	17499	Mopria Print Service wireless printing

Non-wireless A/C Machine Wireless Enabled A/C Machine

A/C Machine	VCI	Temp Probes	VCI	Temp Probes
34288NI, 34788NI, 34788NI-H, 34988NI	80211VCI	80211TMP	ACS-250*	80213 or 80212*
34998, AC1234-9	-	-	ACS-250**	80213 or 80212
AC1234-4	80211VCI	80211TMP	ACS-250*	80213 or 80212*
AC1234-6	_	_	_	_

All machines use 34724 filter and 13172 maintenance kit

*Use of ACS-250, 80212 or 80213 on NI or AC1234-4 requires machine first be WiFi/Bluetooth enabled using either 80211TMP or 80211VCI master kit

**Database purchase required for vehicle refrigerant capacity

Find leaks and diagnose system issues faster





Displacement Compressor Tester

- > Eliminates misdiagnosing electronic variable displacement A/C compressors
- Quickly diagnosis and verify valve function, lowering total repair time and costs
- > Adjustable tester output
- > Includes connect adapters for both old and newer style compressors
- Heavy duty battery clips and cable provides power from vehicle battery, eliminating the need for batteries
- Made in the USA

- Use inexpensive Tracer gas instead of
- costly refrigerant to find leaks Tracer gas is a 95% nitrogen, 5% hydrogen >
- mixture and harmless to A/C systems The LD9-TG detector sniffs out hydrogen,
- detecting leaks faster and at less cost Kit includes 1234yf coupler, 134a coupler,
- Tracer gas detector, hose and Tracer gas regulator
- > Available as LD9-TG, Tracer gas detector only

R-ID Plus refrigerant identifier/ analvzer

- Analyze R-134a and R-1234yf refrigerant for purity and contamination
- Prevent contaminated refrigerant from being pulled into your machine
- Includes printer to add refrigerant purity to service report
- R-134a and R-1234yf tank adapter; R-134a and R-1234yf hoses included
- Available as 16990 R-ID without printer

> Available as LD3 and LD5 versions

Sensor life up to 10 years for

reliable leak detection

> Detects R-1234yf and R-134a leaks for

make finding leaks faster, easier

Features audible detection alert, UV

LED lights for use with UV dye and

Sweep, bar graph and line graph modes

LD7

>

У

leak detector

use on most vehicles

inspection light

NEW NEW

ROBINAIR

> Wirelessly gather and transmit vehicle

9 connected AC machines; will work

have been WiFi/Bluetooth enabled

Requires purchase of refrigerant

capacity, oil type and oil amount

troubleshoot A/C system issues

capabilities on NI and AC1234-4

Includes current-year refrigerant capacity database to quickly determine correct refrigerant charge,

> Also reads generic OBDII codes to

help troubleshoot A/C system issues

oil type and oil capacity

> Wirelessly gather and transmit vehicle year, make and model info to your compatible Robinair machine

Master kit + database

Enables WiFi and Bluetooth

with NI and AC1234-4 machines if they

capacity database to show refrigerant

Also reads generic OBDII codes to help

year, make and model info to your

compatible Robinair machine

ACS-250

80211VCI

machines

3

Robinair VCI

Bluetooth temp probes 80212 2-pack 80213 Single probe

Works directly with 34998 and AC1234-80211TMP

Master kit

- Read and track temperatures from multiple locations from your A/C machine
- 80211TMP master kit enables WiFi and Bluetooth capabilities on NI and AC1234-4 machines and includes 2 probes
- Use up to 2 probes per compatible > Robinair machine
- 80212 / 80213 work directly with 34998 and AC1234-9 connected machines

MUSCLETOOLS

Robinair A/C Tools & Equipment

R-134a Systems

COMBINING SIMPLE OPERATION WITH SUPERIOR ACCURACY

COMBINING SIMPLE OPERATIO	N		R-134a	Systems			R-1234yf	Systems
WITH SUPERIOR ACCURACY These machines will test, recover and recharge R-134a and R-1234yf automotive A/C system quickly and accurately.					Į,	Į,	Ĩ	
Features	34288NI	34788NI	34788NI-H	34988NI	34998	AC1234-4	AC1234-6	AC1234-9
Fully Automatic Function: Program to recover, vacuum, leak test and charge without operating panel valves.	Manual Valves	J	1	1	1	<i>J</i>	7	J
Automatic fluid drain/inject	Oil drain	Oil drain/ inject*	Oil drain	Oil drain/ inject, dye inject**	Oil drain/inject, dye inject**	Oil drain	Oil drain	Oil drain
Refrigerant & Oil Database: A/C system capacities for North American market vehicles (Optional – not included with the machine)	34412-F	34412-F	34412-F	34412-F	34001	34413-D	34414-B	34002
A/C System Flush: Flushes a vehicle's A/C system with refrigerant, eliminating any residual oil or other liquid. (Flushing adapters not included)	-	-	1	1	J	J	1	J
Save & print before and after service data: Allows the user to store before and after service information by vehicle and print this information to provide to a customer.	-	J	1	1	J	J	1	J
Visual & Audible Alarm: Notifies the user when service is complete, or if a problem has occurred.	-	1	1	1	1	J	7	1
Vacuum Leak Test: Monitors level after evacuation, informs of possible leak.	-	1	1	1	1	1	1	1
Automatic Air Purge: Eliminates system-damaging air without monitoring gauges or opening valves.	1	1	1	1	1	1	1	1
Automatic Refrigerant Refill: Maintains a user-selectable amount of refrigerant in an internal vessel and signals when it's time to change supply tank.	-	J	1	1	1	1	1	1
Vacuum Feature: Defaults to 15 mins, programmable up to 99 mins. "Remaining time" is displayed.	1	J	1	1	1	J	J	J
Multilingual display	4.3" color LCD	4.3" color LCD	4.3" color LCD	7" color LCD	10.5" hi-res touch screen	4.3" color LCD	5.7" color LCD	10.5" hi-res touch screen
Refrigerant Charging:	Low only	High, low or both	High, low or both	High, low or both	High, low or both	High, low or both	High, low or both	High, low or both
Refrigerant Management System: Displays refrigerant use and monitors remaining filter life. Prompts appear when 1/3 of filter life remains.	1	1	1	1	J	J	<i>_</i>	1
Electric Vehicle: Capable of servicing high voltage electric compressor A/C systems.	-	-	1	-	-	J	1	1
Printer	30038	30038	30038	Included	Mopria Print Service wireless printing	30038	Included	Mopria Print Service wireless printing
Bluetooth temp probes: Dual-zone temp recording and reporting	80211TMP	80211TMP	80211TMP	80211TMP	80212 or 80213	80211TMP	N/A	80212 or 80213
Bluetooth VCI: Reads YMME and refrigerant capacity	80211VCI	80211VCI	80211VCI	80211VCI	ACS-250***	80211VCI	N/A	ACS-250***

* One oil bottle. ** Two oil bottles and one UV dye bottle. *** ACS-250 requires purchase of 34001 or 34002 database to read YMME and display refrigerant capacity

New 2019 A/C system capacity databases

Vehicle Database Screens R-134a Vehicle A/C Refrigerant Database 2020

- · Confirm A/C system charge capacities directly from your Robinair A/C RRR machine for R-134a and R-1234yf systems, sold separately.
- · Includes charge amounts and component oil capacities for vehicle model years 1997-2020 using R-134a refrigerant and vehicle model years 2013-2020 using R-1234yf refrigerant.
- · Database helps ensure the vehicle system is charged with the correct amount of oil, per factory and OEM specification
- 34001 R-134a database for 34998 R-machine
- 34411-L R-134a database for 34788, 34788-H and 34988 machines
- 34412-F R-134a database for 34288NI, 34788NI, 34788NI-H and 34988NI machines

R-1234yf Vehicle A/C Refrigerant Database 2020

34002 - R-1234yf database for AC1234-9 machine

- 34413-D R-1234yf database for AC1234-4 machine.
- 34414-B R-1234yf database for AC1234-6 machine

Syringe-type Injectors 18480 2 mar 1 18470

Use these syringe-type injectors to add oil to a fully pressurized A/C system. Fill the barrel with the amount of oil needed, connect the injector, and press the plunger.

- 18480 R-134A oil injector, PAG labeled
- 18490 R-134A oil injector, POE labeled
- 18460 R1234YF oil injector, generic
- 18465 R1234YF oil injector, PAG labeled
- 18470 R1234YF oil injector, POE labeled Not recommended for UV dye injection.

Manifolds and Hose Set

R-1234yf Systems



R1234yf Aluminum **Manifolds and Hose Set**

- · Easy-to-read 3-1/8" adjustable gauges.
- · Durable aluminum manifold block with fittings.



· 90° manual couplers • 72" R134a hose set

8

MUSCLETOOLS New Service Stands and Lifts

UNDERHOIST AND SUPPLEMENTARY STANDS WITH A LIMITED LIFETIME WARRANTY

MEETS ASME PASE-2014 SAFETY STANDARDS

UH15 1,500-lb capacity underhoist stand / UH15FP 1,500-lb capacity underhoist stand with foot pedal

- · Threaded rod for easy adjustment lowering and raising to work height
- 11-7/8" flat round base makes full ground contact for stability
- Freestanding support stand aids in R&I of transmissions, radiators, driveshafts, exhaust systems and more
- Not intended to stabilize or support vehicles
- UH15FP includes foot pedal for hands-free adjustment and quickly raises saddle to work height
- UH20 4,000-lb capacity high reach supplementary stand
- · Designed to stabilize vehicles when lifted on hoists
- Extra-sturdy tripod base prevents tipping and leaning
- Secure support column and speed screw for quick adjustment and reliable holding

SPEC	UH15	UH15FP	UH20
Capacity	1,500 lbs	1,500 lbs	4,000 lbs
Max. Height	80.75″	80.75″	85"
Min. Height	54.25"	54.25″	56.25"
Footprint	11-7/8" flat round	11-7/8" flat round	24" triangular tripod base
Adjustment	Threaded rod with T-handle	Foot pedal assist and threaded rod with T-handle	Threaded rod with T-handle
Saddle	5-1/4" x 1-1/4" U-shape	5-1/4" x 1-1/4" U-shape	3-3/16" x 3-3/16" square

Power Train Lifts

- These lifts will handle engine and transmission assemblies, gas tanks, drive axle assemblies, engine/transaxle assemblies, electric vehicle batteries, and more.
- Scissors-type design allows access to all four sides of a component.
- Two independent adjusting screws tilt the table ±15° side-to-side, or fore and aft. Can be operated manually or with non-impact air wrench.
- 20" x 32" table.
- 8" swivel casters provide enhanced mobility under heavy loads.
- ANSI/PALD compliant.

5285

Power train lift (1,650 lb. Capacity)

Air / hydraulic operation - Foot control pump with hose allows movement around lift.

- Min. height is 31-1/2"; Max. height is 74-1/2".
- Footprint 33" wide x 48" long.

1595A

Power train lift (2,500 lb. Capacity)

Powered by an Air/Hydraulic pump.

- Smooth, steady lifting and lowering motion.
- Min. height is 29"; Max. height is 80"
- Footprint 31" wide x 50" long.



UH15FP

UH15

UH20

NEW



	-	nds
GR	SLd	

18





	SA02 (sold as a pair)	S03 (sold as a pair)	SO4 (sold as a pair)
Capacity	2-ton	3-ton	4-ton
Max height	15.44″	17-11/16"	23-13/16"
Min height	9-1/2"	12"	15-1/2″
Footprint	7" round base	8-1/4" x 7-1/2" square base; welded foot pads	Square base; welded foot pads
Adjustment	Pin lock; 6 slots	Ratcheting; 11 teeth	Ratcheting; 11 teeth
Saddle	Flat-top style, 2.17" x 2"	V-notch style, 1" x 3.5"	V-notch style, 1.3" x 4.3"

MUSCLETOOLS New Service Jacks and Stands

Covering the big classes for lifting it all



HDJ5 5-ton hydraulic service jack

- Designed to safely lift step vans and bucket trucks
- 3-position handle lays flat, 45° or 90° for storage and use

HDJ5P 5-ton hydraulic service jack with air-assist

• Same as HDJ5, with air/hydraulic assist to reduce effort to raise, lower vehicles

5, 10, and 20-ton heavy-duty jacks



HDJ10 10-ton hydraulic service jack

- Ideal for bucket trucks and school buses
- Rugged steel frame and extra-large
 wheels for durability and strength

HDJ10P 10-ton hydraulic service jack with air-assist

Same as HDJ10, with air/hydraulic assist to reduce effort to raise, lower vehicles



HDJ20 20-ton hydraulic service jack

- 3-position spring-loaded handle can lay flat, 45° or 90°
- Foot and hand pump options to raise load quickly



5, 10, 20-ton heavy-duty jacks	HDJ5	HDJ5P	HDJ10	HDJ10P	HDJ20
Capacity	5-ton	5-ton air-assist	10-ton	10-ton air-assist	20-ton
Lifting range	6" to 22"	5-7/8" to 22"	6.3" to 22"	6-3/8" to 22"	7-1/2" to 23.8"
Air pressure	-	80-120 PSI	-	80-120 PSI	_
Handle length	43" 3-position with lock and release controls	45.4" 3-position with lock and release controls	43-1/4" 3-position with lock and release controls	45.4" 3-position with lock and release controls	47-1/2", 3-position spring-assisted locking
Footprint	15" x 56"	14.2" x 55.5"	18" x 60"	18.9" x 60.8"	18-1/8" x 61-3/8"
Reach	47″	87″	51″	90″	110.4"
Saddle	5-1/8" dia., round	5.1″ dia., round	6" dia., round	5-3/4" dia., round	6-1/2" dia., steel crown
Casters	4; 4.4" fixed front (2), 2.8" mid-body swivel (2)	4; 4.4" fixed front (2), 2.8" mid-body swivel (2)	4; 5.6" fixed front (2), 3.6" mid-body swivel (2)	4; 5.6" fixed front (2), 3.6" mid-body swivel (2)	6; 4 front fixed; 2 mid-body swivel
Frame height	7.9″	7.5"	9.8"	9.8"	10.2"

MUSCLETOOLS New Service Jacks and Stands



S06 6-ton steel jack stands

Ratcheting design cannot be released under load

- Formed and welded steel base with baked enamel finish for
- strength, corrosion resistance



S022

22-ton steel jack stands

- 11" flat square base prevents sinking into concrete or other surfaces
- Large flat base rated to safely hold up to 44,000 lbs
- Pin Style Stand with 3 adjustment positions

Heavy-duty stands	SO6 (sold as a pair)	S022 (sold as a pair)
Capacity	6-ton	22-ton
Max height	23-11/16"	19-7/8″
Min height	15-5/8"	13-7/8"
Footprint	11-9/16" x 10-3/8" square base; welded foot pads	11" square base, flat for maximum ground contact
Adjustment	Ratcheting; 11 teeth	Pin-style; 3 slots in 3" increments
Saddle	V-notch style, 1.2" x 4.2"	3" x 3-3/4" V-notch



UA22

22-ton under-axle hydraulic service jack

- Includes 3 saddle attachments for height adjustment; 3/4" saddle; 1-15/16" saddle; 3-7/8" saddle
- Self-retracting ram activated with handle-end controls

UA27

27.5-ton under-axle hydraulic service jack

- 4-position, 48" handle allows easy positioning under vehicles
- Two included saddle attachments increase lifting versatility

Under-axle hydraulic service jacks	UA22	UA27
Capacity	22-ton	27.5-ton
Air pressure	90 - 145 PSI	90 - 175 PSI
Max height	20-2/3" with longest saddle	21-3/8" using longest saddle
Min height	8.27"	8-1/4"
Handle length	47.24" T handle with lowering lever and air-chuck hook	48-3/4" T handle with lowering lever and air-chuck hook
Footprint	22.63" x 11.73"	22" x 12"
Reach	69.87"	69.87"
Saddle	3" dia., round with center notch, includes 3 lengths	3" dia., round with center notch. Includes 2 saddle adapters
Frame height	8.27"	8.27"
Wheels	2 fixed; 7.88" rubberized steel	2 fixed; 7.88" rubberized steel

MUSCLETOOLS





1,000 lb. Capacity Engine Stand

- A timesaver for passenger car and light truck engine rebuilding or repair. Four adjustable attachment arms make engine mounting fast and easy.
- · Engine can be rotated a full 360° with a turn of the handle; a locking pin secures the work in any of eight positions.





2,200 lb. Capacity Heavy-Duty Floor Crane

- To conserve valuable floor space, crane folds into a compact package for storage
- · For "close-in" work, leg spread adjusts to clear vehicle's wheels, telescoping boom extension gives additional reach. Roller bearing mounted wheels and steering dolly provide ease of mobility.

39610 – 1/4" steel chain grade 43, 18-3/8" long, 2,200 lb. capacity. Has safety hook on end. Use with 1819



4305

1,500 lb. Capacity Engine Load Leveler

- Designed to hook to a crane or hoist to handle and position large, bulky components.
- · The horizontal tilt can be adjusted to compensate for off-center loads, or adjusted to a certain angle for a component being positioned.

7100

4,000 lb. Capacity Lifting Brackets (pair)

Attach directly to component for easy lifting; will take 1/2" diameter bolts.to a certain angle for a component being positioned.





2,000 lb. Capacity Heavy-Duty Motor-Rotor[®] Repair Stand

- · Handles a wide variety of engines, transmissions, torque converters, and rear axles from trucks, tractors, and construction machinery
- The 50:1 ratio gearbox allows full rotation of mounted unit with just a turn of the crank and locks in position. Easily maneuvered when loaded.



2,000 lb. Capacity Folding Floor Cranes

- Both of these cranes fold up for compact storage.
- Front wheels are 3-1/2"; rear casters 5-7/8".



Load-Rotor[®] Positioning Slings

Use with a floor crane. Engine, transmission, or other component is tilted or leveled by turning sling's 5/8" hex drive end with a common speed handle and socket.

1805 – 2,000 lb. capacity Load-Rotor[®]. Has 56-1/2" long chain (1/4") and hook assembly with forged swiveling hook on each end. Pair of special lifting brackets included.

1806A - 3,900 lb capacity Load-Rotor®. Has 65-3/4" long chain (5/16") and hook assembly with forged hook on each end. Pair of special lifting brackets included.

7118

Transmission Adapter Kit Converts your OTC engine stand into a transmission service stand



206391 6.0L and 6.4L Ford engine adapters Works with both the OTC 1735, 1735A and 1735B

206392 Ford 6.7L Engine Adapter for 1735B HD Rotor **Repair Stand**

Lifting Chains for Floor Cranes

For use with floor cranes only; not recommended for overhead hoists or lifts.

38839 – 1/4" steel chain, 56-1/2" long, 2,000 lb. capacity. Has safety hook on both ends. Use with No. 205049. 38840 - 5/16" steel chain, 65-3/4" long, 4,000 lb. capacity. Has safety hook on both ends. Use with No. 205050.

31609 - 1/4" steel chain, 56-1/2" long, 2,000 lb. capacity. With swiveling safety hooks on both ends. Use with No. 1805.



Alloy Chains for Overhead Lifts and Hoists

302249 - 3/8" alloy chain, 28-3/8" long, 6,000 lb. capacity. With safety hook on one end.

302941 – 5/16" alloy chain, 26-13/16" long, 4,000 lb. capacity. With safety hook on one end. Use on No. 1812



Heavy-Duty Adjustable Slings

For lifting and positioning engines, transmissions, etc. Each chain can be adjusted independently for length; plate design enables chain to be "short-hooked" for correct tilt.

205049 - 2,000 lb. capacity sling with 1/4" chain, 56" long

38841 – Plate only, use with any 1/4" or 5/16" alloy steel chain







THE NEW ONE-HANDED BALLJOINT TOOL MORE MODELS. MORE COVERAGE. MORE VALUE.

ADAPTERS SECURELY CLICK TOGETHER – NO O-RINGS OR WEARABLE PARTS TO LOSE OR REPLACE.





Spring-loaded stainless ball bearings hold adapters during service

NEW



CA7149 Starter Kit

- 7 connected cups & adapters
- 235+ vehicle models covered
- Application guide with adapter callouts



CA6630

- Professional Kit
- 25 connected cups & adapters
- 600+ vehicle models covered
- Fully illustrated manual with adapter callouts, diagrams and instructions by vehicle model



CA6636 C-frame

NEW

- Connected adapter C-frame and forcing screw plug
- Pick and choose your adapters
- Use all your existing OTC adapters with a larger C-frame for more vehicle coverage

14 otctools.com

MUSCLETOOLS

NEW Chrysler, Dodge, Jeep Special Tools



6670

Valve Spring Compressor

A special tool and adapters to properly service valve train components during engine service when cylinder head is on the engine block.

Applications include Chrysler, Mitsubishi, and VW Routan engines. Chrvsler

• 2006-2010 3.0L Diesel

• 2014-Later 3.2L

• 2006-2010 3.5L

• 2011-Later 3.6L

• 2007-2011 4.0L

• 2008-2010 8.4L

2013-2017 8.4L.

• 2006 8.3L

- 2012-Later 1.4L
- 2012-2013 1.4 Multiair
- 2006-2007 1.6L
- · 2006-2013 2.0L
- 2014 2.0L Diesel
- 2006-2010 2.4L
- 2013-Later 2.4L
- 2006-2010 2.7L
- 2006-2014 2.8L Diesel

Mitsubishi 92-Later 3.0L, 3.3L, 3.5L, 3.8L, 5.2L, 8.0L and more engines

Similar to OE part number MLR-MD998772A.



6354

Return Spring Compressor

- This tool is used to compress the 2-4 piston return spring during removal or installation of the retaining ring in automatic transaxles.
- For use on 1989-Later A-604, 41TE, 41AE, 42LE automatic transaxle. Also used on 42RLE transmissions.

Similar to OE part number MLR-5058A



6640

Strut Nut Socket

For use on shock absorbers that have the electrical terminals coming through the center of the tenion and the mounting nut deep into the top mount. A typical socket cannot be used in this application. Tenion must be held with a 9mm open end wrench. This design will allow this interaction to ease the repair. This tool will also work with Passive Absorbers. Hex Size; 18 mm. 1/2" Square Drive.

Vehicles with Electronic and Passive type shock absorbers, including:

For use on 2003-Later 5.9L Cummins Diesel. • Ram Truck 1500 2006-Later

- Chrysler 2006-Later 200, Avenger, Sebring, Town & Country
- Dodge 2006-Later Challenger, Charger, 300, 300C, Magnum, 2008-Later Caravan, Grand Caravan, Journey
- Jeep 2006-Later Compass, Patriot, Caliber, Grand Cherokee
- Mitsubishi 2006-Later Outlander and Raider

Similar to OE part number CH-50732-A and MLR-9362.



Crank Sprocket Installer

Used to install the crankshaft sprocket. Hardened forcing screw may also be used to replace the original 12mm bolt. Includes additional bolt for the 2.7L engine. For use on Chrysler engines:

- 2006 2.0L DOHC
- 2006-2010 2.4L, 2.7L, 3.2L, 3.5
- 2007-2011 4 01
- Similar to OE part number MLR-6792 & MLR-8179.



6782

Leak Check Adapter

A gas tank and gas cap adapter for diagnosing tanks with 1/4 turn type fuel filler caps. Designed to be used with EVAP system tester. Includes a male tank adapter and female cap adapter connected by a 20" hose. Applications include:

- 2006-Later Chrysler/Dodge/Jeep vehicles
- 1999-2003 Mitsubishi Gallant
- 2001-2005 Mitsubishi Eclipse Spyder Similar to OE part number MLR-8382.



6783

Fuel Tank Adapter

A gas tank and gas cap adapter for diagnosing tanks with conventional threaded type fuel filler caps. Designed to be used with EVAP system tester. Includes a male tank adapter and female cap adapter connected by a 40" hose.

Applications include:

- Chrysler 2006-Later Pacifica, Aspen, 200, 200 Convertible, Sebring, Sebring Convertible, 300, 300C, PT Cruiser
- Chrysler 2008-Later Town & Country
- Dodge 2006-Later Durango, Avenger, Nitro, Charger, Magnum, Caliber, Dakota, Sprinter
- Dodge 2008-Later Grand Caravan, Challenger, Journey
- Fiat 2008-Later 500L, Freemont
- · Jeep 2006-Later Wrangler, Liberty, Compass/ Patriot, Grand Cherokee, Commander
- Ram Truck 2006-Later Similar to OE part number MLR-6922.

NEW

6356

Crank Sprocket Remover

- Specialized puller for removing the crankshaft sprocket. Includes three (3) 6mm x 1 x 50mm bolts.
- For use on Chrysler engines 2006 2.0L and 2006-2010 2.4L engines

Similar to OE part number MLR-6793

6359

NEW Power Steering Pulley Puller

Designed for use on power steering pump pulley to prevent damage during pump and pulley removal. Also used to remove alternator pulley on Chrysler vehicles. Applications include:

- Chrysler 2006 2008 Pacifica, Sebring, Town & Country
- Dodge 2006 2008 Stratus, Caravan, Grand Caravan, PT Cruiser
- Jeep 2006 2008 Liberty, Wrangler
- Plymouth 2006 2008 Grand Voyager, Voyager

Similar to OE part number MLR-C-4333A

NEW

6358

Alternator Decoupler Pulley R/I

- This tool holds the alternator shaft in place so the decoupler pulley can be removed and installed. Male and female ends are 10mm.
- Applications include 2004-Later Chrysler/Dodge/Jeep vehicles

Similar to OE part number MLR-8433A.



Ball Joint Remover

6780

- · Designed to separate mainly the lower ball joint from the steering knuckle.
- · Universal design to fit many applications including various 2003-Later Chrysler vehicles. Similar to OE part number MLR-8677



Fuel Pressure Test Adapter

- · Adapts to fuel system for use during pressure testing and diagnostic procedures.
- For use on 2003-Later 5.9L Cummins Diesel.
- Similar to OE part number MLR-9011.



MUSCLETOOLS Bosch EV

Electric Vehicle Charging Solutions

EL-52503 EV400 Series Level 2 charging station

- 25' cable is the longest available for more versatility and installation locations
- NEMA 3R-rated enclosure for indoor or outdoor installation (Outdoor installation requires in-use cover over receptacle)
- SAE J1772 charging connector is compatible with all EVs in North America
- Movable, plug-in installation allows charging when you need it, leaving an open outlet when not charging
- Safely charges in all weather conditions

 rain, snow, sleet, ice and extreme heat
 or cold
- Bracketless mounting for fast and easy installation
- Clear, bright LEDs indicate charging and power status, stop and reset functions



2105_1880_Muscle Tools_Q3 2021 edition, Printed in U.S.A.



EL-50600-D EV810 Series Level 2 charging station

- NEMA4X-rated enclosure is weatherproof for safe charging in any weather or location
- Adjustable charging output allows for installation on circuits as small as 15 Amps, up to 40 Amps
- SAE J1772 charging connector is compatible with all EVs in North America
- Hardwire installation with wall-mount or pedestal options for commercial applications
- Plug-in installation with wall-mount option for household use
- Movable, plug-in installation option allows charging when you need it, leaving an open outlet when not charging

Bosch charging stations are made in the USA from domestic and global components



EL-50650-GNT-B EV850 Series Single bollard charging station

- Includes one EV810 Series charging station in a galvanized steel bollard for parking lot and commercial use - ¼" thick galvanized steel bollard protects against car bumpers, shopping carts and vandalism, protecting your investment
- NEMA4X-rated enclosure is weatherproof for safely charging in any weather or location
- SAE J1772 charging connector is compatible with all EVs in North America
- Hardwire installation and protective bollard creates safe, tamper-proof setup
- Also available as EL-50650-GNT-A EV860 Series Dual bollard charging station with two EV810 Series charging stations in a galvanized steel bollard