NEW STRUT TAMER SAFETY CAGE



- ✓ MEETS THE NEW ASME PASE SAFETY STANDARDS FOR SPRING COMPRESSION
- ✓ SAFETY CAGE FITS STAND OR WALL-MOUNTED STRUT TAMER

STRUT TAMER II EXTREME

The 6637 Strut Tamer II Extreme sets a new standard in strength and safety for strut spring compressors.

- New forged locking jaws includes larger pads and offset to clamp onto and compress springs even tighter than before.
- New extra thick 5/8" compression arms for superior strength, stability and safety.
- New locking trunions for optimal stability during spring compression.
- New Lock rings to hold arms in position - standard. This eliminates arms from spreading or sliding when compressing offset or unique strut configurations. No tools needed to adjust.
- New Spring capacity of 2-1/2" – 10" diameter, 1-1/4" – 24" vertical stroke.
- Extreme duty design to handle the heavier springs found on mid- and some full-size truck strut assemblies.
- 1" structural steel tubing and expanded carbon steel mesh to minimize energy impact of broken or rapidly decompressing coil spring

26031937



Locking trunions increase stability during spring compression

Extra-thick 5/8" compression arms for strength, stability and safety

Stand with wheels for portability (OTC6637-ST only)

During compression, the wheels lift off the floor, and four no-slip rubber pads keep the stand firmly in place

2:1 reduction gearbox - standard. Allows for a 2:1 torque compression increase when compressing struts.

New forged locking jaws include larger pads to clamp and compress springs tighter

Spring capacity of 2-1/2" – 10" diameter, 1-1/4" – 24" vertical stroke

New arm-locking rings hold strong without needing tools to adjust

✓ MEETS THE NEW ASME PASE SAFETY STANDARDS FOR SPRING COMPRESSION

✓ SAFELY COMPRESSES THE LARGEST AUTOMOTIVE SPRINGS

Note: 6637-ST, 6637 can be shipped UPS.

NEW



No. 6637-5
StrutTamer Safety Cage

- 1" structural steel tubing construction provides additional safety layer during compression
- Open design allows access to top and bottom of strut when rebuilding



Strut assembly not included

No. 6637-ST
StrutTamer II Extreme

with stand Height 54" (1372 mm)
(36" without handle)
Width 22-1/2" (572 mm)
Depth 32" (813 mm)



No. 6637
StrutTamer II Extreme

Height 29" (736 mm)
Width 21" (533 mm)
Depth 20" (508 mm)



No. 6582
StrutTamer Stand

Height 44" (1118 mm)
Width 22-1/2" (572 mm)
Depth 32" (813 mm)